

HP P-Series P24 G4 computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD

Gamintojas: HP · Modelis: 1A7E5AA#ABB · EAN: 195122231095 · Prekės kodas: 762575

134,90 €

Kaina su PVM

Be PVM: 111,49 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Navigate documents and spreadsheets and work in applications side by side on the 23.8" (60.45 cm) diagonal Full HD IPS screen with 1920 x 1080 resolution.
- ✓ Quickly connect to your devices and additional displays through the HDMI, DisplayPort™, and VGA connectors.
- ✓ Set a new style standard with a 3-sided micro-edge bezel for unlimited sightlines and virtually seamless multi-display setups. See the screen clearly from almost anywhere with 178° viewing angles.

Aprašymas

Affordable large-screen productivity.

See more of your work onscreen with less window toggling on the HP P24 G4 FHD Monitor. It has business-class presentation features, and advanced connectivity to complement today's workspaces.

Techninė specifikacija

Display	
Display diagonal	60.5 cm (23.8")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Touchscreen	No

HD type	Full HD
Panel type	IPS
Response time	14 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Maximum refresh rate	75 Hz
Display brightness (typical)	250 cd/m²
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1366 x 768, 1440 x 900, 1600 x 900, 1680 x 1050 (WSXGA+)
Contrast ratio (dynamic)	8000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Response time (fast)	5 ms
Pixel pitch	0.274 x 0.274 mm
Colour gamut standard	NTSC
Colour gamut	72%
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No
HP segment	Business
Multimedia	
Built-in speaker(s)	No
Design	
Market positioning	Business
Ports & interfaces	
Built-in USB hub	No
HDMI	Yes
VGA (D-Sub) ports quantity	1
DVI port	No
HDMI version	1.4
DisplayPorts quantity	1
DisplayPort version	1.2
Ergonomics	
VESA mounting	Yes

Cable lock slot	Yes
Height adjustment	No
Panel mounting interface	100 x 100 mm
Tilt angle range	-5 - 23°
Plug and Play	Yes
Power	
Energy efficiency class (SDR)	E
Energy consumption (SDR) per 1000 hours	15 kWh
AC input voltage	100 - 240 V
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Operating relative humidity (H-H)	20 - 80%
Weight & dimensions	
Width (with stand)	538.2 mm
Depth (with stand)	211.6 mm
Height (with stand)	464.3 mm
Weight (with stand)	4.51 kg
Width (without stand)	538.2 mm
Depth (without stand)	45.9 mm
Height (without stand)	325.6 mm
Packaging data	
Package width	598 mm
Package depth	165 mm
Package height	415 mm
Package weight	6.04 kg
Packaging content	
Cables included	AC
Sustainability	
Sustainability certificates	ENERGY STAR
Sustainable technologies and materials	Arsenic-free display glass; Low halogen; Mercury-free display backlights; TCO Certified
Other features	
Country of origin	China
Weight	4.51 kg

Height	325.6 mm
Width	538.2 mm
Depth	45.9 mm
Certification	Australien, Neuseeland MEPS; BSMI; CB; CCC; CE; CEL; CSA; EAC; Energy Star; FCC; ICES; ISO 9241-307; KC; KCC; NOM; PSB; TÜV-S; UL; VCCI; Vietnam MEPS; WEEE; ISC
Logistics data	
Harmonized System (HS) code	85285210
Matmenys ir svoris	
Svoris	4,04kg