

Seagate IronWolf Pro ST30000NT011 internal hard drive 30 TB 7200 RPM 512 MB 3.5" Serial ATA III

Gamintojas: **SEAGATE** · Modelis: **ST30000NT011** · EAN: **8719706435819** · Prekės kodas: **763219**



1 441,90 €

Kaina su PVM

Be PVM: **1 191,65 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Optimized for NAS with AgileArray™ AgileArray enables dual-plane balancing and time-limited error recovery for best-in-class RAID performance in multi-bay systems.
- ✓ Always On, Always Accessible Designed for 24x7 use, allowing users to access their data any time, anywhere.
- ✓ All-CMR Portfolio All IronWolf Pro drives utilize conventional magnetic recording (CMR) technology for consistent, best-in-class NAS performance.
- ✓ Up to 30TB Broad range of capacity options to deliver scalable, cost-efficient storage solutions.
- ✓ Built Tough 550TB/yr workload allows commercial and enterprise NAS users to seamlessly store, share, and collaborate on large amounts of networked data.
- ✓ Class-Leading Reliability and Dependability Rated for 2.5M hours MTBF and include a 5-year limited warranty for hassle-free data storage and best-in-class total cost of ownership.
- ✓ Rotational vibration sensors. Built-in RV sensors for vibration tolerance and consistent performance in multi-bay systems.
- ✓ IronWolf Health Management
- ✓ IHM actively protects your NAS data with prevention, intervention, and recovery recommendations to ensure peak system health.
- ✓ Peace of mind with Data Recovery

Aprašymas

IronWolf Pro is designed for commercial and enterprise NAS.

Delivering Tough, Ready and Scalable 24x7 performance in multibay, multi-user environments

Techninė specifikacija

Specifications

Sandėlio grupė

> Festplatten und SSD > HDD SAS 3,5 [+517][-58]

Features

HDD capacity	30 TB
HDD speed	7200 RPM
HDD size	3.5"
Interface	Serial ATA III
Type	HDD
Component for	NAS
Storage drive buffer size	512 MB
HDD interface transfer rate	6 Gbit/s
HDD sustained transfer rate	275 MiB/s
24/7 operation	Yes
Bytes per sector	512e
Workload rate limit	550 TB/year
Noise level (idle)	28 dB
Mean time between failures (MTBF)	2500000 h

Power

Power consumption (typical)	8.3 W
Power consumption (standby)	1.2 W
Power consumption (idle)	6.8 W
Operating voltage	5 / 12 V
Start-up current	2 A

Operational conditions

Operating temperature (T-T)	10 - 60 °C
Storage temperature (T-T)	-40 - 70 °C
Non-operating vibration	2.27 G
Operating shock	30 G
Non-operating shock	200 G

Weight & dimensions

Width	101.8 mm
Height	26.1 mm
Depth	147 mm
Weight	695 g

Packaging data

Quantity per pack	1 pc(s)
-------------------	---------

Other features

Warranty period	5 year(s)
-----------------	-----------

Matmenys ir svoris

Svoris	0,69kg
--------	--------