

Neewer Z2PRO-N Speedlite Flash for Nikon Cameras

Gamintojas: **NEEWER** · Modelis: **10105411** · EAN: **6976831838560** · Prekės kodas: **763825**



184,90 €

Kaina su PVM

Be PVM: **152,81 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Neewer Z2PRO-N Speedlite Flash for Nikon Cameras

The NEEWER Z2PRO-N is an advanced Speedlite flash designed for Nikon cameras, offering 76Ws of flash power, TTL support, manual mode, HSS up to 1/8000 s, and a high-capacity 7.2V/3000mAh lithium battery. The model is equipped with a modern cooling system that allows for up to 100 full flashes without overheating, as well as a quartz lamp with a lifespan of up to 100,000 flashes. The flash is compatible with a wide range of Nikon cameras (including both Z-series mirrorless cameras and D-SLR digital SLRs) and offers 2.4G wireless communication at a range of up to 100 meters.

Stable light and performance during long sessions

The Z2PRO-N was designed for intensive use, which is why it features an efficient cooling system and a new quartz tube design. This solution allows for up to 100 full continuous flashes without the risk of overheating, which is useful for event coverage, wedding photography, or dynamic shoots. The 76Ws power ensures bright and even lighting of the frame, while the stable color temperature helps preserve natural colors in photos. The swivel head with a 330° rotation range and tilt adjustment from -7° to 120° allows you to conveniently bounce light off walls or the ceiling, making photos look more natural and soft.

Advanced features for greater control over lighting

The NEEWER Z2PRO-N offers full support for TTL, manual, and stroboscopic modes, making it easy to adjust settings for various shooting conditions. The TCM switch allows for an instant switch from TTL to manual mode, streamlining workflow during dynamic shoots. You can manually adjust the

power from 1/1 to 1/256, sync with short HSS shutter speeds up to 1/8000 s, and use first- and second-curtain sync.

Wireless Communication and High-Capacity USB-C Battery

The built-in 2.4G wireless system allows you to control the flash from a distance of up to 100 meters and supports up to 5 groups and 32 channels. The Z2PRO-N can operate as both a master (TX) and slave (RX) unit, making it easier to build more complex lighting setups. The model is also compatible with the Godox X system and select NEEWER accessories, making it easier to expand your photography setup in the future. The 3000mAh lithium battery allows for approximately 600 full flashes on a single charge, and the USB-C port enables convenient charging without the need for a separate charger.

Ecosystem of Accessories and Modifiers

The round flash head is fully compatible with NEEWER accessories and modifiers (including the CRM2, M12, CRS6, CRS7, CRB1, and S2 mount). This allows for quick and easy attachment of magnetic diffusers, barn doors, honeycomb grids, or gel filters, giving you full control over the light’s character.

Compatibility with Nikon Cameras

The NEEWER Z2PRO-N flash was designed specifically for Nikon camera users, ensuring full compatibility with the dedicated i-TTL system and stable wireless communication. The model is compatible with many popular full-frame and APS-C (DX) cameras, making it suitable for both amateur and professional photography.

Included

- NEEWER Z2PRO-N flash
- 3000mAh lithium battery
- USB Type-C cable
- Mini stand
- Protective case
- User manual

Manufacturer	NEEWER
Model	Z2PRO-N
Product type	Speedlite flash
Compatibility	Nikon cameras (including Z9, Z8, Z7 II, Z7, Z6 III, Z6 II, Z6, Z5, Zf, Zfc, Z50, Z30, D6, D5, D850, D780, D750, D500, D7500)
Flash power	76Ws
Operating modes	TTL / Manual / Multi
HSS sync	up to 1/8000 s
Flash power adjustment	1/1 – 1/256
Flash recharge time	approx. 1.5 s
Number of full-power flashes	up to 600
Wireless system	Dual 2.4G (compatible with NEEWER Q and Godox X)
Battery	7.2V / 3000mAh lithium

Charging	USB Type-C
Battery charging time	approx. 2.5 h
Transmission range	up to 100 m
Group support	Master: 4 groups (A/B/C/D) / Slave: 5 groups (A/B/C/D/E)
Channels	32 (and 99 IDs)
Zoom range	28-105 mm (automatic / manual)
Head movement	rotation from 0° to 330°, tilt from -7° to 120°
LED modeling lights	2W, 3300K
Firmware update	via USB-C
Mount	hot shoe (Nikon)
Material	plastic
Dimensions	76 × 76 × 206 mm
Weight	580 g (with battery)

Set: Yes, Adjustable intensity: Yes, GPSR Link: https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf, Last delivery: 16.10.2026, Gross weight: 940, Net weight: 499, Box length: 24,50, Box width: 13,50, Box height: 9,50

Techninė specifikacija

Specifications

Sandėlio grupė Photo and cameras/Photo studio/Lamps [+76][-34]

Matmenys ir svoris

Matmenys (I × P × A) 24,00cm × 13,00cm × 9,00cm

Svoris 0,94kg