

Lindy 4 Port USB 3.2 Gen 2 Type C Hub

Gamintojas: **LINDY** · Modelis: **43414** · EAN: **4002888434140** · Prekės kodas: **765334**



28,89 €

Kaina su PVM

Be PVM: **23,88 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Connects 4 Type C USB peripherals to a Type C port
- ✓ Supports SuperSpeed data rates of up to 10Gbps
- ✓ Handy and stylish design with integrated cable
- ✓ Compatible with all USB Type C equipped computers



Aprašymas

Connect 4 USB Type C devices to a single USB Type C port

The Lindy 4 Port USB 3.2 Gen 2 Type C Hub provides 4 USB Type C 10 Gbps SuperSpeed ports for connecting USB Type C peripherals to a USB Type C equipped computer. As part of the USB 3.2 Gen 2 specification, 10Gbps bandwidth provides lightning fast data transfers between host and mass storage devices. This hub is also backwards compatible with USB 3.2 / 3.1 Gen 1 / USB 3.0 and USB 2.0.

The hub is powered by the USB Bus, while it's functional, stylish design with integrated cable makes it the perfect companion for mobile devices. The Type C connectors reversible design was developed to find a connection regardless of which way the cable is inserted into the port and with Plug & Play installation, no drivers are required, therefore this hub can be installed with minimum difficulty, ideal for both professional and first time users.

*Please note that USB Power Delivery and DisplayPort Alternate Mode (Video) are not supported.

Techninė specifikacija

Specifications	
Sandėlio grupė	USB Hubs [+514][-113]
Ports & interfaces	
Ports quantity	4
Host interface	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
Hub interfaces	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	4
Features	
Data transfer rate	10000 Mbit/s
Product colour	Grey
Housing material	Aluminium, Plastic
Cable type	Round cable
Cable length	0.15 m
Certification	CE, UKCA, FCC, RoHS & REACH, CP65
Power	
Power supply type	USB
Weight & dimensions	
Width	95 mm
Depth	26.4 mm
Height	10.9 mm
Weight	30 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	174 mm
Package depth	20 mm
Package height	194 mm
Package weight	50 g
Package type	Polybag
Packaging content	
Manual	Yes
Operational conditions	
Minimum operating temperature	-25 °C

Maximum operating temperature	40 °C
Operating temperature (T-T)	-25 - 40 °C
Operating temperature (T-T)	77 - 104 °F
Storage temperature (T-T)	-25 - 85 °C
Operating relative humidity (H-H)	60 - 95%

Technical details

Warranty period	2 year(s)
Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS