

Lindy USB 3.2 Type A to C adapter

Gamintojas: **LINDY** · Modelis: **41904** · EAN: **4002888419048** · Prekės kodas: **765431**



7,90 €

Kaina su PVM

Be PVM: **6,53 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Turn a USB Type A port into a USB Type C port to connect peripherals with USB Type C connector to devices with built-in USB Type A ports
- ✓ Robust TPE housing, nickel connectors and gold plated contacts
- ✓ Compact size, perfect for use in discreet installations
- ✓ Supports data transfer speeds up to SuperSpeed USB 10Gbps (USB 3.2 Gen 2, backwards compatible with USB 2.0, 1.1)
- ✓ 10 year warranty



Aprašymas

USB adapters allow users to connect different USB interfaces to a device that uses a differing USB port.

The Lindy USB 3.2 Type A to C adapter is a compact, useful adapter that allows users to connect a device with USB Type C connection to a USB Type A port.

Data transfer speeds up to 10Gbps are supported for the quick and effortless transfer of large data volumes.

Techninė specifikacija

Specifications

Sandėlio grupė	USB Hubs [+514][-113]
----------------	-----------------------

Ports & interfaces

Connector 1	USB 3.2 Type A
-------------	----------------

Connector 2	USB 3.2 Type C
-------------	----------------

Connector 1 gender	Male
--------------------	------

Connector 2 gender	Female
--------------------	--------

Connector 1 form factor	Straight
-------------------------	----------

Connector 2 form factor	Straight
-------------------------	----------

Connector contacts plating	Nickel/Gold
----------------------------	-------------

Performance

Product colour	Black
----------------	-------

Housing material	Thermoplastic elastomer (TPE)
------------------	-------------------------------

Data transfer rate	10 Gbit/s
--------------------	-----------

Plug and Play	Yes
---------------	-----

Operational conditions

Operating temperature (T-T)	-10 - 60 °C
-----------------------------	-------------

Storage temperature (T-T)	-20 - 75 °C
---------------------------	-------------

Certificates

Compliance certificates	REACH, RoHS
-------------------------	-------------

Weight & dimensions

Width	24 mm
-------	-------

Depth	15 mm
-------	-------

Height	9 mm
--------	------

Packaging content

Quantity per pack	1 pc(s)
-------------------	---------

Packaging data

Package type	Polybag
--------------	---------