

iiyama TE6513A-B1AG Signage Display Interactive flat panel 163.8 cm (64.5") Wi-Fi 500 cd/m² 4K Ultra HD Black Touchscreen Built-in processor Android 18/7

Gamintojas: IIYAMA CONSIGNMENT · Modelis: TE6513A-B1AG · EAN: 4948570124800 · Prekės kodas: 765811



1 582,90 €

Kaina su PVM

Be PVM: 1 308,18 €

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Indoor Interactive flat panel Black
- ✓ Ethernet LAN Wi-Fi
- ✓ 163.8 cm (64.5") 3840 x 2160 pixels 500 cd/m²
- ✓ Built-in speaker(s) 60 W
- ✓ Touchscreen 60 Hz 8 ms



Aprašymas

The TE6513A-B1AG is a cutting-edge 4K UHD Google EDLA Certified interactive display that redefines performance and precision. Featuring a Zero-Gap Air Bonding LCD screen to eliminate parallax and with PureTouch-IR+ with Palm Rejection, it ensures smooth, accurate interaction. Powered by iiWare 21E with Android 14-EDLA, WiFi-6 with Bluetooth 5.0 connectivity, iControl (DMS), iiShare and integrated EShare app (wireless screen sharing), it integrates seamlessly into your ecosystem. Enjoy added features like a PIR motion sensor for energy efficiency; perfect for workplaces and educational spaces, it fosters collaboration, communication, and progress.

Techninė specifikacija

Specifications

Sandėlio grupė	Displays > Lcd Touchscreen [+81][-96]
----------------	---------------------------------------

Display

Display diagonal	163.8 cm (64.5")
Display resolution	3840 x 2160 pixels
Display brightness	500 cd/m²
HD type	4K Ultra HD
Touchscreen	Yes
Panel type	IPS
Touchscreen technology	PureTouch-IR
Number of simultaneous touchpoints	40
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Pixel pitch	0.372 x 0.372 mm
Active display area (W x H)	1428.5 x 803.5 mm
Display diagonal (metric)	163.9 cm
Horizontal scan range	30 - 135 kHz
Native refresh rate	60 Hz
Surface hardness	7H
Glass thickness	3.2 mm

Ports & interfaces

HDMI ports quantity	3
DisplayPorts quantity	1
USB port	Yes
HDMI version	2
HDMI input ports quantity	1
HDMI output ports quantity	1
DisplayPort version	1.2
USB ports quantity	6
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	2

USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	100 W
USB Type-C DisplayPort Alternate Mode	Yes
Ethernet LAN (RJ-45) ports	2
RS-232C	Yes
OPS module slot	Yes
Audio Return Channel (ARC)	Yes
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	60 W
Design	
Product design	Interactive flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal
Panel mounting interface	600 x 400 mm
Bezel colour	Black
Anti-glare screen	Yes
Positioning accuracy	1 mm
Performance	
Purpose	Education
On Screen Display (OSD)	Yes
Number of OSD languages	13
On Screen Display (OSD) languages	Czech, Danish, German, English, Spanish, Estonian, Finnish, French, Hungarian, Italian, LAT, Norwegian, Dutch, Polish, Russian, Swedish, Ukrainian
Operating hours (hours/days)	18/7
HDCP	Yes
HDCP version	2.2
Mean time between failures (MTBF)	50000 h
Power	
Power consumption (typical)	182 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W

Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	182 kWh
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
Computer system	
Computer system	Yes
Built-in processor	Yes
Processor architecture	ARM Cortex-A73
Processor frequency	1.4 GHz
Processor cores	4
Internal memory	8 GB
On-board graphics card model	ARM Mali-G52
Internal storage capacity	128 GB
Operating system installed	Android
Operating system version	14
Weight & dimensions	
Display width	1489 mm
Display depth	87 mm
Display height	891.5 mm
Display weight	39.4 kg
Width	1489 mm
Depth	87 mm
Height	891.5 mm
Weight	39.4 kg
Packaging data	
Package width	1640 mm
Package depth	185 mm
Package height	1010 mm
Package weight	48.5 kg
Packaging content	
Remote control included	Yes
Stylus pen	Yes

Number of stylus pens	4
Cables included	AC, USB, HDMI
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Ethernet LAN data rates	1000 Mbit/s
Wi-Fi standards	Wi-Fi 6 (802.11ax)
Technical details	
OPS slot	1
Sustainability certificates	ErP
Compliance certificates	CB, CE, EAC, REACH, RoHS, TÜV mark, WEEE
Audio in (mini jack)	Yes
Playback media	Y
User controls	general settings (input, volume, backlight), audio (volume, bass, treble, balance, sound mode, mute), screen settings (aspect ratio, pixel shift), display settings (brightness, contrast, hue, sharpness, display mode colour temp), settings (wireless & networks, share, device, personal, system)
Warranty period	5 year(s)
Other features	
Quick start guide	Yes
Bluetooth	Yes
Bluetooth version	5
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Power supply type	Internal
Matmenys ir svoris	
Matmenys (I × P × A)	163,00cm × 102,00cm × 18,00cm
Svoris	47,80kg