

TP-Link AC1200 Wi-Fi Tinklo kartotuvus Balta 10, 100 Mbit/ai

 Gamintojas: **TP-LINK** · Modelis: **RE315** · EAN: **6935364072445** · Prekės kodas: **766010**


40,90 €

Kaina su PVM

 Be PVM: **33,80 €**


Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Tinklo kartotuvus 867 Mbit/ai
- ✓ 10/100Base-T(X)
- ✓ „Wi-Fi“ Dviguba juosta (2,4 GHz / 5 GHz) 1167 Mbit/ai 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
- ✓ Balta



Aprašymas

 Expand Dual Band WiFi Everywhere
 AC1200 Mesh WiFi Extender

Boost Whole Home WiFi with Your Existing Router

A single router has limited WiFi coverage and always causes WiFi dead zones. RE315 wirelessly connects to your existing router and expands its WiFi signal into areas it can't reach on its own. Enjoy your stable network experience wherever you are at home.

WiFi keeps Strongest for Unlimited Moving

With TP-Link Mesh Technology, it's easy to form a Mesh network with a single WiFi name for seamless whole home coverage. Just connect RE315 to a OneMesh™ router. Always enjoy the strongest WiFi when you're walking around with no need to search around for a stable connection.

Enjoy a Mesh Network with Your Existing Router

Want a Mesh network? Hesitate on whether to replace your existing router and buy a Mesh set?

TP-Link OneMesh™ resolves your dilemma.

Faster Dual Band WiFi up to 1200 Mbps

RE315 delivers dual band (2.4 GHz and 5 GHz) to transmit WiFi signals, doubling the performance of each band. It enables you to keep more devices connected at the same time with its 300 Mbps 2.4 GHz and 867 Mbps 5 GHz dual bands. Use the 2.4 GHz band to send email and browse the web and the 5 GHz band for gaming and HD streaming.

Adaptive Path Selection: Keeps Itself Working at Top Speed

Adaptive Path Selection keeps your network running at optimal speeds by automatically choosing the fastest connection path to the router. Always keep your devices fast and stable—ideal for network environments crowded with many devices and applications.

High Speed Mode: Maximized Speed with Dedicated Backhaul

Uses one dedicated WiFi band as backhaul and another dedicated WiFi band as an access point to maximize the bandwidth on the extended WiFi.

Built-In Access Point Mode

RE315 is more than a wireless range extender. Simply plug an Ethernet cable into its Ethernet port and easily turn your wired internet connection into a 2x2 MIMO dual band wireless access point.

Secure One-Touch Connection for Easy Setup

Step 1: Simply press the WPS button on your router and, within 2 minutes, the WPS button on RE315 will connect to the network.

Step 2: Once connected, place RE315 at the best location—without reconfiguration.

Find the Best Location with the Smart Signal Indicator

The smart signal indicator lets you see signal strength from the existing router at a glance. Easily to find the best place to position your range extender to extend your WiFi.

Control at Your Fingertips

Set up and manage your WiFi through the TP-Link Tether app from your smartphone (Android, iOS), including TP-Link routers and range extenders.

Techninė specifikacija

Performance

Type	Network repeater
------	------------------

Data transfer rate	867 Mbit/s
Ethernet LAN data rates	10,100 Mbit/s
WPS push button	Yes
Windows operating systems supported	Yes
Mac compatibility	Yes
Mac operating systems supported	Yes
Linux operating systems supported	Yes
Browser supported	Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0
Antenna	
Antennas quantity	2
Antenna type	External
Transmitting power (CE)	2.4 GHz ≤20dBm, 5 GHz ≤30dBm
Network	
Ethernet LAN interface type	Fast Ethernet
Cabling technology	10/100Base-T(X)
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Wi-Fi	Yes
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Wi-Fi data rate (max)	867 Mbit/s
Wi-Fi band	Dual-band (2.4 GHz / 5 GHz)
WLAN data transfer rates supported	300 Mbit/s
Security algorithms	64-bit WEP, 128-bit WEP, WPA-PSK, WPA2-PSK
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Design	
Product colour	White
LED indicators	Yes
Quantity per pack	1 pc(s)
Reset button	Yes
Certification	CE, RoHS
Power	
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz

Power consumption (max)	9.5 W
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Weight & dimensions	
Width	89 mm
Depth	35 mm
Height	124.1 mm
Packaging content	
Quick start guide	Yes
Packaging data	
Package type	Box
Package width	121.5 mm
Package depth	89 mm
Package height	156.5 mm
Package weight	260 g
Certificates	
Compliance certificates	CE, RoHS
Logistics data	
Harmonized System (HS) code	85176990
Matmenys ir svoris	
Matmenys (I × P × A)	13,00cm × 16,00cm × 9,00cm
Svoris	0,28kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Greitos pradžios vadovas](#)
- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas 1](#) [objects.icecat.biz/objects/87591882_18424185.mp4](#)
- › [Vaizdo įrašas 2](#) [objects.icecat.biz/objects/87591882_18424188.mp4](#)
- › [Vaizdo įrašas 3](#) [objects.icecat.biz/objects/87591882_18424192.mp4](#)
- › [Vaizdo įrašas 4](#) [youtube.com/watch?v=wiHiv-TByjc](#)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederkasseler Lohweg 175, 40547 Düsseldorf,
DE

[tp-link.com](https://www.tp-link.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt