

APC AP7921B power distribution unit (PDU) 8 AC outlet(s) 0U/1U Black

Gamintojas: **APC** · Modelis: **AP7921B** · EAN: **731304331629** · Prekės kodas: **766411**



1 433,90 €

Kaina su PVM

Be PVM: **1 185,04 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Metered, Switched 0U/1U Black
- ✓ 8 AC outlet(s) C13 coupler
- ✓ 3680 W



Aprašymas

This APC Switched Rack PDU power distribution unit has a wide range of standardized PDU features that increase network efficiency, manageability and functionality. The output and input connections are (8)C13. Network management capabilities allow you to configure and manage rack PDUs from remote locations. It has has a local current monitoring display that gives a visible warning in case of an overload. The remote individual outlet control provides real-time monitoring of connected loads. It has a multi-tier user access that enables you to restrict unauthorized use of outlets. This rack has a single input power source making it easy to install.

Techninė specifikacija

Design

PDU types

Metered, Switched

Rack capacity	0U/1U
Mounting	Horizontal/Vertical
Product colour	Black
Ports & interfaces	
AC outlets quantity	8 AC outlet(s)
AC outlet types	C13 coupler
Power plug	C20 coupler
Input connection type	IEC-320 C20
Features	
Cable length	2.5 m
Management features	
Monitoring	Current, Power, Voltage
Outlet control	Lock-out, Recycle, Turn off, Turn on
Power	
Nominal input voltage	200-230 V
Maximum current	16 A
AC input frequency	50 - 60 Hz
Nominal output voltage	208-230 V
Load capacity	3680 VA
Maximum input current per phase	16 A
Maximum total current draw per phase	16 A
Maximum power	3680 W
Certificates	
Compliance certificates	RoHS
Certification	cUL Listed, CE, CSA, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, GOST, IRAM, MIC, UL 60950, UL Listed, VDE, VCCI, REACH
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-25 - 65 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	1 - 15000 m
Weight & dimensions	

Width	445 mm
Depth	108 mm
Height	44 mm
Weight	2.27 kg
Packaging content	
Packaging content	Installation Guide, Rack Mounting Brackets, User Manual
Packaging data	
Package weight	3.45 kg
Package width	470 mm
Package depth	343 mm
Package height	70 mm
Logistics data	
Total carbon footprint (kg of CO2e)	915.89

Dokumentai ir vaizdo įrašai

- [Naudojimo instrukcija](#)
- [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR
[se.com](https://www.se.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt