D-Link DGS-1100-18PV2 network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Black

Gamintojas: **D-LINK** · Modelis: **DGS-1100-18PV2** · EAN: **790069453366** · Prekės kodas: **766430**

266,90 €

Kaina su PVM

Be PVM: **220,58 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Gigabit Ethernet Speeds
- ✓ Cutting Edge Green Technology
- ✓ Manage Anywhere, Anytime

Aprašymas

Powerful Switching for your Business

The DGS-1100 Series is a range of powerful switches that offer a lot of bang for your buck. They are great for busy SMBs who expect a lot of their network, including support for surveillance and VoIP. They are packed with traffic management & optimization features that keep your network congestion free. Meanwhile, management tools are flexible and intuitive, making your life easier.

Easy to Use & Easy to Install

D-Link Network Assistant Utility (DNA) can quickly discover and do initial setup for D-Link Networking devices such as the DGS-1100 Series, which greatly improves efficiency for solution deployment.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

VLANs: Stronger Security & Better Traffic Management

Relatively easy to set up, VLANs can be a big boon for your network. They can isolate sensitive areas of your network, keeping them safe from those with malicious intent, or keeping bandwidth open for latency-sensitive traffic such as VoIP.

Green Technology

D-Link Green technology enables the DGS-1100 Smart Managed Switches to save power without sacrificing performance. Most of the models in the series utilize a fanless design, for silent and energy-efficient operation. All are IEEE 802.3az-compliant and feature Link Status detection and Time-Based PoE.

PD Alive Actively Mitigates Downtime

Round-the-clock surveillance footage is vital. If you have Cameras attached to your network,
you may have thought technical difficulties were a given. However, the PD-Alive feature actively mitigates device downtime. If a device is not working as expected, the Switch can automatically reset them and get them back online. No need to turn them on and off again in the middle of the night.

Techninė specifikacija

Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Combo SFP ports quantity	2
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	1000BASE-T
Full duplex	Yes
Half duplex	Yes
Flow control support	Yes
Link aggregation	Yes
Auto MDI/MDI-X	Yes
Spanning tree protocol	Yes
Ethernet LAN data rates	10,100,1000 Mbit/s
Auto-negotiation	Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

VLAN support	Yes
Number of VLANs	4094
Data transmission	
Switching capacity	36 Gbit/s
Forwarding rate	26.78 Mpps
Jumbo frames support	Yes
Jumbo frames	9216
Security	
IGMP snooping	Yes
Design	
Rack mounting	Yes
Form factor	1U
Product colour	Black
Number of fans	1 fan(s)
Electromagnetic compatibility	FCC Class A, CE Class A, VCCI Class A, C-Tick, BSMI
Performance	
Noise level	45.8 dB
Mean time between failures (MTBF)	343695 h
Power	
Power source	DC/PoE
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	16
Total Power over Ethernet (PoE) budget	130 W
Operational conditions	
Operating temperature (T-T)	-5 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Heat dissipation	125.2 BTU/h
Weight & dimensions	

Width	280 mm
Depth	230 mm
Height	44 mm
Weight	2.1 kg
Certificates	
Compliance certificates	RoHS
Certification	cUL, UL, LVD, CB, BSMI

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux
Postbus 48, 5480 AA Schijndel, NL
dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.