

Zebra LI3608 Handheld bar code reader 1D Black, Green

Gamintojas: **ZEBRA** · Modelis: **LI3608-SR3U4600VZW** · EAN: **4016139084626** · Prekės kodas: **766460**



398,90 €

Kaina su PVM

Be PVM: **329,67 €**

[Sandėlyje](#)



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Handheld bar code reader Black, Green
- ✓ Scanner type: 1D
- ✓ Codabar, Code 11, Code 128, Code 25 (non-IR 2 of 5), Code 39, Code 93, GS1-128 (UCC/EAN-128), U.P.C.
- ✓ Tilt reading angle: -65 - 65°
- ✓ Wired Standard interfaces: USB, RS-232, Bluetooth
- ✓ Power source type: Battery Lithium-Ion (Li-Ion) 3100 mAh



Aprašymas

Unstoppable performance for 1D barcode capture

Every day, workers in your warehouse and on the manufacturing plant floor scan thousands of barcodes to ensure product quality and on-time order delivery. Their productivity depends on the quality of the scanner you put in their hands. When workers need to capture 1D barcodes, you can give them the best with the 1D corded LI3608 and cordless LI3678 scanner. Both models offer unmatched durability, superior scanning performance and unrivaled manageability, while delivering lightning-fast capture of any 1D barcode printed on a label in virtually any condition, or displayed on a screen. The ultra-rugged design is practically indestructible — ideal for punishing environments. The LI3608/LI3678 couldn't be easier and less time-consuming to deploy and manage. And when it comes to cordless technology, the

LI3678 is in a class of its own, with a complete solution that includes a sealed rugged cradle, a smart battery and Zebra's Wi-Fi Friendly Mode that prevents interference with your Wi-Fi network. Get the unstoppable performance you need to maximize workforce productivity and throughput in

your operations with the LI3608/LI3678 — only from Zebra.

Superior scanning performance on any 1D barcode, in any condition

Read 1D barcodes displayed on a screen or printed on a label faster than any other 1D scanner on the market — even if they are under heavy shrinkwrap or damaged, dirty or poorly printed. The advanced linear imager offers 30 percent more working range than competitive devices, and captures barcodes as fast as your workers can pull the trigger for extraordinary productivity — no need to pause between scans.

Ultra-rugged — the most indestructible design in its class

The LI3608/LI3678 is our most rugged scanner yet, with the highest drop, tumble and sealing specification in its class. The LI3608/LI3678 is built to survive an 8 ft./2.4 m drop to concrete — 23 percent more durable than any other scanner in this class. The LI3608/LI3678 operates reliably after 5,000 tumbles, simulating the real-world tumbling that occurs with a drop. Both models are dustproof, sprayproof and waterproofed to IP67 — they can be sprayed down with jetting water and even submersed in water for up to 30 minutes.

Easy management with our complimentary industry-best tools

Remotely configure scanners, upgrade firmware, format data properly for your back end and monitor PowerPrecision+ battery statistics and more with 123Scan and Scanner Management Service (SMS).

Crispest aiming pattern in its class

You get the industry's sharpest, brightest aiming pattern, ideal for first-time accurate capture of barcodes in pick lists.

Three flexible feedback modes

Mix and match the feedback modes that are ideal in your environment — vibration, red and green LEDs located in an area where they are always easy to see, plus the traditional loud beep tone.

Extreme temperature rating

Built to handle extreme cold, heat and humidity, you can use the LI3608/LI3678 anywhere — even in the freezer.

A Bluetooth model in a class of its own for superior cordless freedom

Bluetooth 4.0 (Low Energy) provides lightning fast wireless communication and maximum energy efficiency.

Our Zebra Wi-Fi Friendly Mode eliminates the wireless interference that Bluetooth devices can often create in your Wi-Fi environment.

The 'go anywhere' rugged cradle offers superior versatility and durability. The LI3678 cradle is the only one in its class to offer IP65 sealing. And its industrial charging contacts withstand 250,000 insertions.

The first-in-its-class battery 'charge gauge' and Bluetooth status LED make it easy to monitor battery power and Bluetooth connectivity.

The PowerPrecision+ battery delivers the ultimate in battery power and management. You get 56 percent more scans-per-charge compared to similar models in its class, plus visibility into

a wealth of battery health-related data, including charge cycles consumed, current battery status and a State of Health meter, which identifies if batteries are healthy and holding a full charge, no longer holding a full charge, or at end of life and require replacement.

Techninė specifikacija

Scanning

Type	Handheld bar code reader
------	--------------------------

Scanner type	1D
Linear (1D) barcodes supported	Codabar, Code 11, Code 128, Code 25 (non-IR 2 of 5), Code 39, Code 93, GS1-128 (UCC/EAN-128), U.P.C.
2D (matrix & stacked) barcodes supported	Not supported
Tilt reading angle	-65 - 65°
Pitch reading angle	-65 - 65°
Yaw reading angle	-45 - 45°
Optical sensor resolution	1500 pixels

Ports & interfaces

Connectivity technology	Wired
Standard interfaces	USB, RS-232, Bluetooth
Data transfer rate	3 Mbit/s
Wireless range	100 m
PC connection	RS-232

Performance

Product colour	Black, Green
International Protection (IP) code	IP65
Protection features	Shock resistant
LED indicators	Yes
Certification	EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011 + AC 2011 + A2: 2013, IEC 60950-1: 2005 + A1: 2009 + A2: 2013, UL 60950-1, second edition, CAN/CSA-C22.2 No. 60950-1-07, IEC 62471: 2006 (Ed.1.0); EN 62471: 2008 (LED), EN 55022: 2010/AC: 2011 (Class B), EN 55024: 2010, EN 61000-6-2: 2005/AC:2005, EN 61000-3-2: 2006 + A1: 2009 + A2: 2009 (Class B), EN 61000-3-3: 2013, EN 60601-1-2: 2007/AC: 2010, IEC 60601-1-2: 2007 (Modified), 47 CFR Part 15, Subpart B, Class B, ICES-003 Issue 5, Class B

Power

Power source type	Battery
Battery technology	Lithium-Ion (Li-Ion)
Battery capacity	3100 mAh
Input voltage	4.5 - 5.5 V

Weight & dimensions

Weight	287 g
Width	132 mm
Depth	76 mm
Height	185 mm

Packaging data

Cables included	USB
Operational conditions	
Operating temperature (T-T)	-30 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Technical details	
Compliance certificates	RoHS
Logistics data	
Harmonized System (HS) code	84716070

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Zebra

ATSAKINGAS ASMUO ES

Zebra Technologies

Borupvang 3, Ballerup, DK
zebra.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt