



# UPS ERA PLUS DC POE 24VDC/FGCERAPLDC252 TECNOWARE



Modelis: FGCERAPLDC252

Gamintojas: TECNOWARE

EAN: 8026475177988

Prekės kodas: 76660

## 64.99€

UPS ERA PLUS DC 9VDC / 12VDC - POE 24VDC / 48VDC - USB 5VDC TOGETHER ON, 8,800 mAh batteries, It has Black-Out, overvoltage and undervoltage protection. DC technology. Dimensions 16x2,8x10,5cm, weight 0,5 kg. Equipped with On-Off button with integrated multifunction LED for signaling the operating status. Designed to protect devices such as WIFI, Modem / router, VOIP, Cameras and recharge of devices such as Tablet, SmartPhone, Bluetooth headphones, Smartwatch and etc. Totally silent.

- Complete protection from black outs and voltage surges (overvoltages and undervoltages)
- Designed to protect devices such as WIFI, Modem / router, VOIP, Cameras and etc
- Charging of devices such as Tablet, SmartPhone, Bluetooth headphones , Smartwatch and etc
- Equipped with On-Off button with multifunction LED
- Lithium batteries from 8.800 mAh
- POE function to add power on the LAN cable

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

- Output connections: DC 5.5x2, 5 mm - RJ45 - USB
- Wide compatibility thanks to the 10 Tips included in the package

Summary: Tecnoware FGCERAPLDC252. UPS topology: Standby (Offline), Output power: 18 W, Input operation voltage (min): 110 V. Battery technology: Lithium-Ion (Li-Ion), Battery capacity: 8800 Ah, Typical backup time at full load: 240 min. Product colour: Black, International Protection (IP) code: IP20. Width: 160 mm, Depth: 105 mm, Height: 28 mm. Package width: 170 mm, Package depth: 140 mm, Package height: 35 mm | Vendor Homepage: <https://www.tecnoware.com/en-US/Dettaglio/Articolo/644> | Input frequency: 50/60 | Input operation voltage (max): 240 | Input operation voltage (min): 110 | Noise level: 40 | Number of input phases: 1 | Number of output phases: 1 | Output operation voltage (min): 5 | Output power: 18 | UPS topology: Standby (Offline) | Ethernet LAN (RJ-45) ports: 1 | USB port: Yes | Battery capacity: 8800 | Battery technology: Lithium-Ion (Li-Ion) | Typical backup time at full load: 240 | International Protection (IP) code: IP20 | LED indicators: Yes | Product colour: Black | Operating altitude: 0 - 3000 | Operating temperature (T-T): 0 - 55 | Depth: 105 | Height: 28 | Weight: 500 | Width: 160 | Package depth: 140 | Package height: 35 | Package width: 170 | Model: FGCERAPLDC252 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.001917 | Unit Calculated Weight: 0.61

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903