



Switch UBIQUITI Pro Max 16 Type L3 USW-PRO- MAX-16



Modelis: USW-PRO-MAX-16

Gamintojas: UBIQUITI

EAN: 810084694565

Prekės kodas: 76721

277.99€

A 16-port, Layer 3 Etherlighting™ switch 2.5 GbE and versatile mounting options.

- Etherlighting™ ports that illuminate to indicate port location, speed/link, and native VLAN/network*
- (4) 2.5 GbE RJ45 ports
- (12) GbE RJ45 ports
- (2) 10G SFP+ ports
- Versatile desktop, wall, and rack** mounting
- Silent, fanless cooling system

Summary: Ubiquiti Pro Max 16. Switch layer: L3. Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500), Basic switching RJ-45 Ethernet ports quantity: 16. MAC address table: 16000 entries, Switching capacity: 84 Gbit/s. Networking standards: IEEE 802.1x. Power connector: AC/DC. Rack mounting, Form factor: 1U | Vendor Homepage:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

<https://eu.store.ui.com/eu/en/pro/products/usw-pro-max-16> | Quality of Service (QoS) support: Yes | Switch layer: L3 | 2.5G Ethernet (copper) ports quantity: 4 | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Gigabit Ethernet (copper) ports quantity: 12 | Power connector: AC/DC | SFP+ module slots quantity: 2 | 10G support: Yes | Broadcast storm control: Yes | Flow control support: Yes | IPv4 routes: 512 | Link aggregation: Yes | Networking standards: IEEE 802.1x | Number of VLANs: 1000 | Port mirroring: Yes | Rate limiting: Yes | Virtual LAN features: Voice VLAN | VLAN support: Yes | Forwarding rate: 62 | Jumbo frames support: Yes | MAC address table: 16000 | Packet buffer memory: 1.5 | Static route: Yes | Switching capacity: 84 | Throughput: 42 | Access Control List (ACL): Yes | Authentication type: IEEE 802.1x | DHCP features: DHCP guarding/DHCP relay/DHCP server/DHCP snooping | IGMP snooping: Yes | Loop protection: Yes | Display type: LCM | Form factor: 1U | Housing material: SGCC | LED indicators: Link/Network/Speed/Status | Product colour: Grey | Rack mounting: Yes | Reset button: Yes | Stackable: Yes | Fanless: Yes | Input current: 5 | Input voltage: 4.8 - 5.2 | Power consumption (max): 25 | Power supply included: Yes | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): No | Heat dissipation: 85.3 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 40 | Depth: 160 | Height: 43.7 | Weight: 1950 | Width: 325.1 | Cables included: Power | Rack mount kit: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC)/National Defense Authorization Act (NDAA) | Model: USW-Pro-Max-16 | Model name: Pro Max 16 | Units per Shipping Box: 4 | Unit Calculated Volume: 0.0167344 | Unit Calculated Weight: 3.4625

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903