

TP-Link 10/100Mbps Single-Mode Media Converter

Gamintojas: **TP-LINK** · Modelis: **MC110CS** · EAN: **6935364030407** · Prekės kodas: **767419**



47,90 €

Kaina su PVM

Be PVM: **39,59 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Complies with 802.3u 10/100Base-TX, 100Base-FX standards
- ✓ Link Fault Passthrough and Far End Fault minimize the loss caused by link failure timely
- ✓ Provides switch configuration of Half-Duplex / Full-Duplex transfer mode for FX port
- ✓ Extends fiber distance up to 20km

Aprašymas

What This Product Does

The MC110CS is a media converter designed to convert 100BASE-FX fiber to 100Base-TX copper media or vice versa. Designed under IEEE 802.3u 10/100Base-TX and 100Base-FX standards, the MC110CS is designed for use with single-mode fiber cable utilizing the SC-Type connector. The MC110CS supports longwave (LX) laser specification at a full wire speed forwarding rate. It works at 1310nm on both transmitting and receiving data.

Other features of this module include the ability to be used as a stand alone device (no chassis required) or with TP-LINK's 19" system chassis, Auto MDI/MDI-X for TX port, Auto negotiation of duplex mode on TX port and front panel status LEDs. The MC110CS will transmit at extended fiber optic distances utilizing single-mode fiber up to 20 kilometers.

Techninė specifikacija

Network

Maximum data transfer rate	1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Ethernet interface type	Gigabit Ethernet

Ethernet LAN data rates	1000 Mbit/s
Fiber ethernet cabling technology	100BASE-FX
Auto MDI/MDI-X	Yes
Cabling technology	UTP 3, 4, 5e, 5
Cable types supported	Cat3, Cat4, Cat5, Cat5e
Performance	
Maximum transfer distance	20000 m
Wavelength	1310 nm
Features	
Internal	No
LED indicators	Power, Speed
Product colour	Black
Compliance industry standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Ports & interfaces	
Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Power consumption (max)	1.52 W
Weight & dimensions	
Width	94.5 mm
Depth	73 mm
Height	27 mm
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Packaging data	
Package width	165 mm
Package depth	204 mm
Package height	65 mm
Package weight	380 g

Certificates

Certification	FCC, CE
---------------	---------

Other features

Dimensions (WxDxH)	94.5 x 73 x 27 mm
--------------------	-------------------

Full duplex	Yes
-------------	-----

I/O ports	1x 100M SC 1x 100M RJ45
-----------	-------------------------

Dokumentai ir vaizdo įrašai

[› Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

TP-Link

ATSAKINGAS ASMUO ES

TP-Link Deutschland GmbH

Niederlasser Lohweg 175, 40547 Düsseldorf,

DE

tp-link.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt