

CyberPower PDU24004 power distribution unit (PDU) 12 AC outlet(s) 1U Black

Gamintojas: **CYBERPOWER** · Modelis: **PDU24004** · EAN: **4711027799810** · Prekės kodas: **768720**



484,90 €

Kaina su PVM

Be PVM: **400,74 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Real-time Local Monitoring
- ✓ Quick Transfer Time (Total $\leq$ 10 ms)
- ✓ Digital Real-time Load Display
- ✓ Hot-swappable LCD Design
- ✓ Firmware Upgrade via USB
- ✓ Adjustable Mounting Brackets
- ✓ IEC Receptacle Locking
- ✓ Dual Inputs
- ✓ Industrial-grade Metal Housing
- ✓ User Configurable Color LCD



Aprašymas

CyberPower PDU24004 provides output from a UPS unit, generator, or utility power to multiple connected devices in IT environments. Dual power cords can be plugged into separate power sources to provide redundancy to single-corded connected equipment. If the selected power source exceeds the desired thresholds or fails, the ATS PDU will automatically switch to the other power source to ensure continuous operation.

The unit comes with a hot-swappable multifunction readout that displays real-time vitals including current, input voltage, power consumption levels in amps and watts. The digital LCD display is also color configurable, allowing easy maintenance and monitoring of the ATS PDU. Users can change LCD's colors to easily categorize devices between multiple machines in server room and IT environments. The firmware can also be conveniently upgraded via the USB port, ensuring the latest features and updates are available for users.

Techninė specifikacija

Design		
PDU types		Managed, Switched
Rack capacity		1U
Type		Single-phase
Form factor		Rackmount
Mounting		Horizontal
Housing material		Steel
Product colour		Black
Display		LCD
On/off switch		Yes
Ports & interfaces		
AC outlets quantity		12 AC outlet(s)
AC outlet types		C13 coupler
Power plug		IEC 60320
Ethernet LAN (RJ-45) ports		1
USB ports quantity		1
Features		
Daisy chain		Yes
LED indicators		Yes
Cable length		3.05 m
Management features		
Monitoring		Current, Power, Voltage
Power		
Nominal input voltage		200 - 240 V
Maximum current		12 A
AC input frequency		50 - 60 Hz
Certificates		
Compliance certificates		CE, RoHS
Certification		CE, FCC Class A, UL62368, EN 55032 Class A, IEC 62368
Operational conditions		
Operating temperature (T-T)		0 - 45 °C
Storage temperature (T-T)		-15 - 55 °C
Operating relative humidity (H-H)		0 - 95%

Storage relative humidity (H-H)	0 - 95%
---------------------------------	---------

Operating altitude	0 - 15000 m
--------------------	-------------

Weight & dimensions

Width	433 mm
-------	--------

Depth	215 mm
-------	--------

Height	44 mm
--------	-------

Weight	3.5 kg
--------	--------

Packaging data

Package weight	5.7 kg
----------------	--------

Package width	550 mm
---------------	--------

Package depth	398 mm
---------------	--------

Package height	125 mm
----------------	--------

Logistics data

Country of origin	China
-------------------	-------

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Matmenys ir svoris

Svoris	5,48kg
--------	--------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

CyberPower

ATSAKINGAS ASMUO ES

Cyberpower Systems GmbHEdisonstr. 16, 85716 Unterschleissheim, DE
[cyberpower.com](https://www.cyberpower.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt