

InLine 92501K wire connector Terminal block / D-Sub 9 Green

Gamintojas: **INLINE** · Modelis: **92501K** · EAN: **4043718345953** · Prekės kodas: **769555**



25,89 €

Kaina su PVM

Be PVM: **21,40 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Terminal block / D-Sub 9 Female/Female
- ✓ 1 pc(s)
- ✓ Green



Aprašymas

Time savings during installation: Quick wiring via screw terminals for 14-26 AWG – tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Stable connection thanks to mounting thread: The D-Sub-9 receptacle is equipped with a mounting thread (UNC #4-40) for plug locking and ensures a secure connection to matching plugs.

Versatile use in industry: Ideal for control cabinet construction, machine control, automation, and service and diagnostic environments.

DIN rail mounting for structured installations: The integrated DIN rail clip allows direct mounting in the control cabinet – space-saving and compliant with standards.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 0.8 A per pin ensure reliable signal transmission in

professional applications.

The InLine® D-Sub 9 terminal block with female connector has been specially developed for structured installations in control cabinets or on DIN top-hat rails. The side-accessible screw terminals with pressure plate mounting enable quick wiring of single wires in the 14–26 AWG range, without any soldering. Assembly is tool-assisted with a flat-head screwdriver ≤ 2.5 mm.

Thanks to the mounting thread (UNC #4-40), the socket can be mechanically secured with matching connectors. The housing design with integrated DIN rail clip allows quick mounting on DIN rails. The EVA insulating layer on the underside provides additional protection when mounting on conductive surfaces.

D-Sub 9 female connector: Breakout design, with mounting thread for connector locking (UNC #4-40)

Connection technology: Screw terminal with pressure plate

Connection range: 14–26 AWG

Actuation: With flat-blade screwdriver ≤ 2.5 mm

Rated current: 0.8 A per pin

Max. operating voltage: 100 V between two signals

Insulation resistance: ≥ 10 M Ω @ 300 V DC

Operating temperature: -10 °C to +70 °C

Insulation layer: EVA insulation on underside

Mounting: Housing for direct mounting on DIN rail

Dimensions: approx. 87 × 46 × 51 mm (L × W × H)

Techninė specifikacija

Features	
Connector(s)	Terminal block / D-Sub 9
Product colour	Green
Connector gender	Female/Female
Dielectric strength	300 V
Contact resistance	10 m Ω
Voltage	100 V
Current	0.8 A
Operational conditions	
Operating temperature (T-T)	-10 - 70 °C
Certificates	
Compliance certificates	RoHS, TÜV mark
Weight & dimensions	
Dimensions (WxDxH)	46 x 87 x 51 mm
Weight	77 g
Width	46 mm
Depth	87 mm
Height	51 mm

Packaging data

Quantity per pack	1 pc(s)
Package width	95 mm
Package depth	120 mm
Package height	55 mm
Package weight	122 g
Package volume	100 cm ³
Package type	Polybag

Logistics data

Country of origin	Taiwan
-------------------	--------

Gamintojo ir saugos informacija

GAMINTOJAS

Intos Electronic AG

Siemensstraße 11, D-35394 Gießen, DE

service@inline-info.com

[intos.de](https://www.intos.de)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt