

Dahua Technology WizSense HDW3649H-AS-PV-PRO Turret IP security camera Indoor & outdoor 3200 x 1800 pixels Ceiling/wall

Gamintojas: **DAHUA** · Modelis: **HDW3649H-ASPV0280BPRO-B** · EAN: **6939554948350** · Prekės kodas: **769608**



415,90 €

Kaina su PVM

Be PVM: **343,72 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 6-MP 1/1.8" CMOS image sensor, low luminance, and high definition image
- ✓ Outputs max. 6 MP (3288 × 1850)@25/30 fps
- ✓ H.265 codec, high compression rate, ultra-low bit rate
- ✓ Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 30 m. · ROI, SMART H.264+/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- ✓ Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Intelligent monitoring: Intrusion, tripwire (the two function support the classification and accurate detection of vehicle and human)
- ✓ Abnormality detection: Motion detection, privacy masking, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- ✓ Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 512 G Micro SD card; built-in dual Mic; 1-ch speaker; support two-way talk
- ✓ 12 VDC/PoE power supply
- ✓ IP67 protection



Aprašymas

6MP Smart Dual Light Active Deterrence Fixed-focal Eyeball WizSense Network Camera

Techninė specifikacija

Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Alarm input/output	Yes
Design	
Mounting type	Ceiling/wall
Product colour	Black
Form factor	Turret
Housing material	Metal
International Protection (IP) code	IP67
Camera	
Minimum illumination	0.0003 lx
Angle of rotation	360°
Lens viewing angle, horizontal	109°
Lens viewing angle, vertical	59°
Lens viewing angle, diagonal	131°
Tilt angle range	0 - 78°
Pan range	0 - 360°
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp
Camera shutter type	Electronic
Camera shutter speed	1/100000 s
Number of Privacy masking areas	8
Image sensor	
Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 1.8 mm (1 / 1.8")
Progressive scan	Yes
Lens system	
Number of lenses	1
Detect distance	4.4 m

Fixed focus	Yes
Fixed focal length	3.6 mm
Night vision	
Night vision	Yes
Night vision distance	30 m
LED type	IR/White
Number of illumination LEDs	2
Video	
Maximum resolution	3200 x 1800 pixels
Total megapixels	6 MP
Video compression formats	H.264, H.264+, H.264B, H.264H, H.265, H.265+, M-JPEG
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1536 x 2048, 1920 x 1080 (HD 1080), 2304 x 1296, 2560 x 1440, 2688 x 1520, 2880 x 1620, 3200 x 1800
Frame rate	30 fps
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes
Smart IR	Yes
Audio	
Audio input channels	1.0 channels
Audio output channels	1.0 channels
Audio formats supported	G.711 A-law, G.711 μ -law, G.723, G.726, PCM
Signal-to-Noise Ratio (SNR)	56 dB
Built-in microphone	Yes
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet

Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP
Number of users	20 user(s)
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
ROM capacity	128 MB
RAM capacity	512 MB
Security	
Alarm input channels	1
Alarm output channels	1
Video motion detection	Yes
Security algorithms	HTTPS
Intelligent Video Surveillance (IVS) system features	Intrusion, Tripwire
Mirror	Yes
Digital watermark	Yes
Management features	
Web-based management	Yes
Management software	Smart PSS; DSS; DMSS
Power	
Power source type	DC, PoE
Power consumption (typical)	3.7 W
Power consumption (max)	8.3 W
Power consumption (Power over Ethernet (PoE))	4.8 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
System requirements	
Mobile operating systems supported	Android, iOS
Weight & dimensions	

Height	110.9 mm
Diameter	12.2 cm
Weight	745 g
Packaging data	
Package weight	915 g
Packaging content	
Number of cameras	1
Matmenys ir svoris	
Matmenys (l × P × A)	16,00cm × 16,00cm × 14,00cm

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Zhejiang Dahua Technology Co., Ltd

Bin'an Road, Binjiang District No.1187 & 1199,
310053 Hangzhou, CN
dahuasecurity.com

ATSAKINGAS ASMUO ES

Dahua Technology GmbH

Niederkasseler Lohweg 185, 40547 Düsseldorf,
DE
dahuasecurity.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt