

APC Smart-UPS On-Line nepertraukiamo maitinimo resursai (UPS) Dviguba konversija (prisijungus) 5 kVA 4500 W 10 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **SRT5KRMXLI** · EAN: **731304301196** · Prekės kodas: **769790**



6 190,90 €

Kaina su PVM

Be PVM: **5 116,45 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dviguba konversija (prisijungus)
- ✓ 5 kVA 4500 W
- ✓ Signalų forma: Sinusas
- ✓ 10 AC išvestis(ys / čių)
- ✓ Rūgštinis akumulatorius (VRLA)
- ✓ Stelažas Juoda





Aprašymas

Stay always online and prevent data loss

An APC Smart-UPS On-Line always supplies perfectly clean power to all connected equipment thanks to its double conversion technology. Even power outages have no influence on this. The APC Smart-UPS On-Line then automatically supplies emergency power without having to switch. This way you prevent unwanted failure of, for example, a PC, server, storage or switch. With the included Powershute Network Shutdown software you can even have critical IT hardware shut down in an automated and controlled manner. This prevents data loss, downtime and physical damage to hardware.

Extend the runtime

You can easily increase the number of minutes that the APC SRT5KRMXLI can independently supply emergency power by connecting external battery packs (SRT192RMBP). A runtime of several hours is even possible.

Availability

The Smart-UPS On-Line has an internal bypass and uses double conversion, maximizing the availability and lifespan of connected hardware. It also makes the UPS compatible with an emergency power generator. The On-Line double conversion technology ensures clean, uninterrupted power to protected equipment even when generator power is used.

Safety

In addition, a Smart-UPS On-Line protects connected devices against peak voltage caused by lightning, among other things. This APC emergency power supply is ideally suited for business use.

Rack mount

The APC Smart-UPS SRT is easy to operate in the rack thanks to a tiltable graphic LCD screen. Thanks to the included 4-post rail kit, you can easily mount the UPS in a rack.

Manage your Smart-UPS

Thanks to the integrated network card, you can easily connect the APC UPS to the network. This way you can monitor and manage the UPS remotely (SNMP) and the UPS can send a shutdown signal to multiple physical and/or virtual servers using PowerChute Network Shutdown software.

PowerChute Network Shutdown

PowerChute Network Shutdown is UPS management software that works with the UPS Network Management Card to protect Windows, Linux and Host ESXi, as well as hyperconverged and virtual infrastructure*. In the event of a power outage, PowerChute can properly shut down your virtual machines and the preconfigured boot sequence ensures they are turned back on.

*An additional license is required for HCI and virtual machine support:

1 year: SWPCNS1Y-DIGI

3 years: SWPCNS3Y-DIGI

5 years: SWPCNS5Y-DIGI

Remote management and monitoring of your network

The network card can be managed remotely via the easy-to-use web browser interface, remote management software EcoStruxure™ IT (SFTWES1-DIGI) or other SNMP-compatible system. Tip EcoStruxure™ IT also includes the functionalities of the support contract below.

Support contract

The optional network card support contract license* ensures you are always up to date and secure and includes additional benefits such as frequent updates with:

- New and improved features
- Security updates
- Advanced support

*The above license is available in the variants:

1 year: SWNMC3SU-1Y-DIGI

3 years: SWNMC3SU-3Y-DIGI

5 years: SWNMC3SU-5Y-DIGI

Extend the lifespan

The internal battery cartridge (APCRBC140) can be replaced easily, safely and independently by the user. This without having to switch off the APC SRT5KRMXLI or connected equipment. This way you can easily and cheaply extend the lifespan of the APC Smart-UPS and your equipment always remains online.

Warranty extension

The manufacturer's warranty of the SRT5KRMXLI is 3 years, with the exception of the battery cartridge, which has a 2-year manufacturer's warranty. Both are extended by 3 years to 6 and 5 years respectively with the APC service pack (WBEXTWAR3YR-SP-05).

Maximize availability

Or instead of extending the warranty, opt for the even more complete 5-year Monitoring & Dispatch Service (WMD5YOSNBD-SP-05) to maximize the availability of your APC UPS. In addition to a 5-year warranty, it also includes 24/7 remote monitoring through the Schneider Electric Connected Services Hub and SE's on-site repair service (replacement parts, labor, installation and call-out charges).

Switched Outlet Groups: Remote reboot and phased start-up

Thanks to the Switched Outlet Groups, it is possible to configure a phased/delayed power-on per UPS outlet group. This reduces the peak load on the UPS and brings it closer to the constant load, which limits oversizing of the UPS.

It is also possible to reset a group of multiple UPS outputs and the equipment connected to them. If a network card (ap9640) is used in combination with Ecostruxure IT Expert (SFTWES1-DIGI), this can even be done remotely.

You can also eliminate non-critical loads; Like this extend the runtime for critical equipment.

Green Premium

This label represents Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises to comply with the latest regulations, transparency on environmental effects and circular and low CO2 emission products.

Green Premium:

- Stands for an energy-efficient product that helps our customers achieve their CO2 reduction goals and save energy costs at the same time. The energy efficiency of this product is at least 10% higher than the market average.
- Provides insight into the environmental effects of the product, this data is available 24/7 via the digital product environmental profile, see <https://checkaproduct.se.com/>
- Commits to minimal use of hazardous substances within and beyond regulatory compliance (RoHS/REACH)

Included in the box

- 1x SRT5KRMXLI
- 1x C13 to C14 power cord 1.2 meters
- 1x C13 to C14 power cord 2 meters
- 1x PowerChute Network Shutdown (CD)
- 1x Installation manual
- 1x Rack mounting brackets
- 1x temperature sensor (AP9335T)
- 1x USB cable
- 1x 2.5MM to DB9 cable

Techninė specifikacija

Features	
UPS topology	Double-conversion (Online)
Output power capacity	5 kVA
Output power	4500 W
Waveform	Sine
Input operation voltage (min)	100 V
Input operation voltage (max)	275 V
Input frequency	40 - 70 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency regulation	50/60 Hz
Surge energy rating	480 J
Efficiency	94.1%
Crest factor	3:1
Emergency Power Off (EPO)	Yes
Output voltage Total Harmonic Distortion (THD)	3%
Noise level	55 dB
Surge protection	Yes
Audible alarm(s)	Yes
Auto-restart	Yes
Ports & interfaces	

AC outlet types	C13 coupler, C19 coupler
Power plug	Hardwire
AC outlets quantity	10 AC outlet(s)
Number of output IEC jumpers	2
USB port	Yes
Serial interface	Yes
Serial interface type	RJ-45
Ethernet LAN (RJ-45) ports	0
SmartSlot	Yes
SmartConnect port	No

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	845 VAh
Typical backup time at full load	4 min
Typical backup time at half load	11.8 min
Battery life (max)	5 year(s)
Battery recharge time	1.5 h
Hot-swap battery	Yes
Automatic battery test	Yes
Cold start	Yes
Replacement battery cartridge	APCRBC140

Design

Form factor	Rackmount
Product colour	Black
Rack capacity	3U
Display type	LCD

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Compliance certificates	RoHS
Certification	REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, RCM, VDE
Packaging content	
Rack mount kit	Yes
Management card included	Yes
Quick installation guide	Yes
Sustainability	
Sustainability certificates	ENERGY STAR
Weight & dimensions	
Width	432 mm
Depth	719 mm
Height	130 mm
Weight	54.4 kg
Packaging data	
Temperature sensor	Yes
Warranty card	Yes
Package width	610 mm
Package depth	960 mm
Package height	330 mm
Package weight	66.9 kg
Logistics data	
Products per pallet	6 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	8408.59
Other features	
Packaging content	Web/SNMP Management Card
Matmenys ir svoris	
Matmenys (I × P × A)	95,00cm × 61,00cm × 32,00cm
Svoris	69,40kg

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 Reuil Malmaison, FR

se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt