

CyberPower RMCARD205 tinklo plokštė Vidinis Eternetas 100 Mbit/ai

Gamintojas: **CYBERPOWER** · Modelis: **RMCARD205** · EAN: **4712364141089** · Prekės kodas: **769799**



156,90 €

Kaina su PVM

Be PVM: **129,67 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vielinis
- ✓ Greitas eternetas 100 Mbit/ai 10/100
- ✓ Eternetas
- ✓ Vidinis



Aprašymas

A full-featured network management card, the CyberPower RMCARD205 remotely manages, monitors, and controls CyberPower OR and PR Series UPS systems and ATS PDUs via a standard web browser or network management system (NMS) connection. Especially suited to enterprise installations where the administrator might not be onsite, the RMCARD205 provides scheduling for UPS shutdown, startup, and rebooting, along with event action settings, event logging, and automatic event notification sent via Email, SMS, SNMP Traps, or Syslog. Our PowerPanel® Business Edition Client auto-shutdown software protects servers and workstations from data loss due to power failure. The MD5 security management safeguards the integrity of the network.

An optional environmental sensor (ENVIROSENSOR) can be added to RMCARD205 to monitor the ambient temperature and humidity of a server room, IT closet, or other critical environment. Administrators define temperature parameters in Fahrenheit or Celsius; rising temperatures will prompt the RMCARD305 to send a predefined notification. The RMCARD205 comes with a three-year warranty.

Techninė specifikacija

Features	
Product type	Network management card
Product colour	Black, Blue
Performance	
Web-based management	Yes
Management protocols	TCP/IP, UDP, FTP, DHCP, DNS, SSH, Telnet, HTTP/HTTPS, SNMPv1/v3, IPv4/v6, NTP, SMTP, Syslog, RADIUS, LDAP, LDAPS, and Windows Active Directory
Supported network protocols	IPv4/v6, SNMPv1/v3, HTTP/HTTPS, TCP/IP, UDP, DHCP, NTP, DNS, SMTP, SSH, SSL, TLS, Telnet, FTP, and Syslog
Syslog	Yes
Ports & interfaces	
Interface type	RJ-45
Ethernet LAN (RJ-45) ports	2
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Cabling technology	10/100
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Weight & dimensions	
Width	54 mm
Depth	76.5 mm
Height	36.1 mm
Weight	38 g
Packaging content	
Cables included	Serial
Quantity per pack	1 pc(s)

Quick start guide	Yes
-------------------	-----

Packaging data

Package width	168 mm
---------------	--------

Package depth	164 mm
---------------	--------

Package height	58 mm
----------------	-------

Package weight	250 g
----------------	-------

Logistics data

Country of origin	China
-------------------	-------

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Matmenys ir svoris

Matmenys (l × P × A)	16,00cm × 17,00cm × 6,00cm
----------------------	----------------------------

Svoris	0,25kg
--------	--------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)
- › [Vaizdo įrašas 1](#) youtube.com/watch?v=wYY05nJ-JmU
- › [Vaizdo įrašas 2](#) youtube.com/watch?v=2dTNCRwtbTk

Gamintojo ir saugos informacija

GAMINTOJAS

CyberPower

ATSAKINGAS ASMUO ES

Cyberpower Systems GmbHEdisonstr. 16, 85716 Unterschleissheim, DE
cyberpower.com

PLATINTOJAS

MB KOMPIUTERIŲ GURUV. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt