

InLine 92504L wire connector 6.35 mm 3-pin jack TRS / Terminal block 3 terminals Black, Green

Gamintojas: **INLINE** · Modelis: **92504L** · EAN: **4043718346219** · Prekės kodas: **769852**



15,90 €

Kaina su PVM

Be PVM: **13,14 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Male/Female Straight
- ✓ 1 pc(s)
- ✓ Black, Green

Aprašymas

Time savings during installation: Quick wiring via screw terminals for 18–26 AWG – tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Precise contacting of audio signals: 3-pin 6.35 mm jack plug (TRS) with clearly assigned terminals (L, R, +) – ideal for professional audio or control cables in prototyping, measurements, or control engineering.

Side terminal strip for space-saving installation: Adjacent terminals in a 5.0 mm grid allow for compact integration – e.g., in audio distributors, test boxes, or signal converters.

Versatile use in industry: For analog signal wiring in laboratories, control modules, audio interfaces, or multimedia applications with 6.35 mm interfaces.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of up to 1 A per pin ensure reliable signal transmission – even in continuous operation.

The InLine® 6.35 mm TRS jack plug (stereo, 3-pin) on terminal block offers a solderless solution for connecting analog audio signals – e.g. in control lines, test setups, or prototypes. The screw terminals with pressure plate are aligned laterally and enable fast, tool-assisted wiring in the 18–26 AWG range.

The terminal assignment is clearly marked: L (left), R (right), + (common ground/shielding). The compact design is also suitable for applications with limited space, such as in rack systems, distributors, or mobile test fields. The EVA insulation layer on the underside provides protection when mounted on a conductive surface.

Jack connection: 6.35 mm TRS jack plug (3-pin, stereo)

Number of poles / terminal assignment: 3 terminals / L, R, +

Connection technology:Screw terminal with pressure plate, 5.0 mm pitch

Connection range:18–26 AWG

Actuation:With flat-blade screwdriver ≤ 2.5 mm

Rated current:1.0 A per pin

Max. operating voltage:70 V between two signals

Insulation resistance: $\geq 10\text{ M}\Omega$ @ 300 V DC

Max. conductor resistance:5 ohms

Operating temperature:-10 °C to +70 °C

Insulation layer:EVA insulation on underside

Techninė specifikacija

Features	
Connector(s)	6.35 mm 3-pin jack TRS / Terminal block 3 terminals
Product colour	Black, Green
Connector gender	Male/Female
Connector form factor	Straight
AWG wire size	26/16
Dielectric strength	300 V
Contact resistance	10 m Ω
Voltage	70 V
Current	1 A
Operational conditions	
Operating temperature (T-T)	-10 - 70 °C
Certificates	
Compliance certificates	RoHS, TÜV mark
Weight & dimensions	
Weight	16 g
Width	21 mm
Depth	80 mm
Packaging data	
Quantity per pack	1 pc(s)
Package volume	100 cm ³
Package type	Polybag
Logistics data	
Country of origin	Taiwan

Gamintojo ir saugos informacija

GAMINTOJAS

Intos Electronic AG

Siemensstraße 11, D-35394 Gießen, DE

service@inline-info.com

[intos.de](https://www.intos.de)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt