

Dahua Technology WizSense HDBW3541R-ZAS-27135-S2 security camera Dome IP security camera Outdoor 2960 x 1668 pixels Ceiling/wall

Gamintojas: **DAHUA** · Modelis: **HDBW3541R-ZAS-27135-S2** · EAN: **6923172542267** · Prekės kodas: **770829**



161,90 € ~~435,90 €~~

Kaina su PVM

Be PVM: **133,80 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 5MP 1/2.7" CMOS image sensor, excellent low luminance performance and high definition of images
- ✓ Outputs max. 5 MP (2960 × 1668) @20 fps and supports 4MP (2688 × 1520) @25/30 fps
- ✓ H.265 codec, high compression rate, ultra-low bit rate
- ✓ Built-in IR LED, max. IR distance: 40 m
- ✓ ROI, SMART H.264 +/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- ✓ Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- ✓ Abnormality detection: Motion detection, privacy masking, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- ✓ Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); max. 256 G Micro SD card; built-in Mic
- ✓ 12 VDC/PoE power supply, easy for installation



Aprašymas

- 5MP 1/2.7" CMOS image sensor, excellent low luminance performance and high definition of images
- Outputs max. 5 MP (2960 × 1668) @20 fps and supports 4MP (2688 × 1520) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED, max. IR distance: 40 m
- ROI, SMART H.264 +/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, privacy masking, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); max. 256 G Micro SD card; built-in Mic
- 12 VDC/PoE power supply, easy for installation
- IP67, IK10 protection
- SMD 4.0, AI SSA

Summary: Dahua Technology WizSense HDBW3541R-ZAS-27135-S2. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: Black, White, Form factor: Dome. Angle of rotation: 355°, Lens viewing angle, horizontal: 114 - 32°, Lens viewing angle, vertical: 58 - 17°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Focal length range: 2.7 - 13.5 mm, Focus: Motorized, Detect distance (wide): 64 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/WizSense-Series/3-Series/5MP/IPC-HDBW3541R-ZAS-S2=S2> | Form factor: Dome | Mounting type: Ceiling/wall | Product colour: Black/White | Housing material: Metal | International Protection (IP) code: IP67 | IK code: IK10 | Fog proof: Yes | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | Dynamic range: 120 | Minimum illumination: 0 | Angle of rotation: 355 | Lens viewing angle, horizontal: 114 - 32 | Lens viewing angle, vertical: 58 - 17 | Lens viewing angle, diagonal: 138 - 36 | Tilt angle range: 0 - 80 | Pan range: 0 - 355 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter type: Electronic | Camera shutter speed: 1/3 - 1/100000 | Adjustment shutter speed: Auto/Manual | Number of Privacy masking areas: 4 | Number of sensors: 1 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Number of lenses: 1 | Focal length range: 2.7 - 13.5 | Focus: Motorized | Minimum aperture number: 1.5 | Closest focusing distance: 0.8 | Detect distance (tele): 210 | Detect distance (wide): 64 | Identify distance (tele): 21 | Identify distance (wide): 6.4 | Observe distance (tele): 84 | Observe distance (wide): 25.6 | Recognize distance (tele): 42 | Recognize distance (wide): 12.8 | Night vision: Yes | Night vision distance: 40 | LED type: IR | Number of illumination LEDs: 3 | Maximum resolution: 2960 x 1668 | Total megapixels: 5 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2048 x 1536 (QXGA)/2304 x 1296/2560 x 1440/2688 x 1520/2880 x 1620/352 x 240/352 x 288/640 x 480 (VGA)/704 x 480/704 x 576 | Frame rate: 30 | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto | Back Light Compensation (BLC): Yes | Bit rate: H.264: 3 kbps-8192 kbps H.265: 3 kbps-8192 kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Image stabilizer: Yes | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Smart IR: Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Signal-to-Noise Ratio (SNR): 56 | Built-in microphone: Yes | Voice codecs: G.711a/G.711Mu/G.723/G.726/PCM | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.3af | Supported network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; | Wi-Fi: No | Bluetooth: No | Number of users: 20 | Quality of Service (QoS) support: Yes | Streaming method: Multicast | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | Internal memory: 512 | ROM capacity: 128 | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 1 | Alarm output channels: 1 | Mirror: Yes | Web-based management: Yes | Web browser: Yes | Behavior analysis: Intrusion detection | Power source type: DC, PoE | Power consumption (typical): 4 | Power consumption (max): 9.2 | Power consumption (Power over Ethernet (PoE)): 4.9 | DC output voltage: 12 | Operating temperature (T-T): -30 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Mobile operating systems supported: Android/iOS | Height: 122 | Diameter: 94 | Weight: 713 | Package weight: 986 | Number of cameras: 1 | Unit Calculated Weight: 0.867 | Product Net Weight: 0.713 | Unit Calculated Volume: 0.006868 | Units per Shipping Box: 30 | Unit Width: 19 | Units per Pallet: 0 | Shipping Box Height: 36 | Unit Depth: 19 | Unit Height: 16.5 | Name: NET CAMERA 5MP IR DOME/HDBW3541R-ZAS-27135-S2 DAHUA | Model: IPC-HDBW3541R-ZAS-27135-S2

Techninė specifikacija

Performance

Type	IP security camera
------	--------------------

Placement supported	Outdoor
Connectivity technology	Wired
Dynamic range	120 dB
Design	
Mounting type	Ceiling/wall
Product colour	Black, White
Form factor	Dome
Housing material	Metal
International Protection (IP) code	IP67
IK code	IK10
Fog proof	Yes
Camera	
Minimum illumination	0 lx
Angle of rotation	355°
Lens viewing angle, horizontal	114 - 32°
Lens viewing angle, vertical	58 - 17°
Lens viewing angle, diagonal	138 - 36°
Tilt angle range	0 - 80°
Pan range	0 - 355°
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp
Camera shutter type	Electronic
Camera shutter speed	1/3 - 1/100000 s
Adjustment shutter speed	Auto/Manual
Number of Privacy masking areas	4
Image sensor	
Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Progressive scan	Yes
Lens system	
Number of lenses	1
Focal length range	2.7 - 13.5 mm
Focus	Motorized
Minimum aperture number	1.5

Detect distance (wide)	64 m
Detect distance (tele)	210 m
Observe distance (wide)	25.6 m
Observe distance (tele)	84 m
Recognize distance (wide)	12.8 m
Recognize distance (tele)	42 m
Identify distance (wide)	6.4 m
Identify distance (tele)	21 m
Closest focusing distance	0.8 m
Night vision	
Night vision	Yes
Night vision distance	40 m
LED type	IR
Number of illumination LEDs	3
Video	
Maximum resolution	2960 x 1668 pixels
Total megapixels	5 MP
Video compression formats	H.264, H.264B, H.264H, H.265, M-JPEG
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2304 x 1296, 2560 x 1440, 2688 x 1520, 2880 x 1620
Frame rate	30 fps
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Image stabilizer	Yes
Gain control type	Auto
Privacy masking	Yes
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Bit rate	H.264: 3 kbps-8192 kbps H.265: 3 kbps-8192 kbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes
Smart IR	Yes
Audio	
Audio input channels	1.0 channels

Audio output channels	1.0 channels
Signal-to-Noise Ratio (SNR)	56 dB
Built-in microphone	Yes
Voice codecs	G.711Mu, G.711a, G.723, G.726, PCM
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Networking standards	IEEE 802.3af
Supported network protocols	IPv4; IPv6; HTTP;TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP;
Number of users	20 user(s)
Quality of Service (QoS) support	Yes
Streaming method	Multicast
Storage	
Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB
Internal memory	512 MB
ROM capacity	128 MB
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Security	
Alarm input channels	1
Alarm output channels	1
Mirror	Yes
Management features	
Web-based management	Yes
Web browser	Yes
Behavior analysis	Intrusion detection
Power	
Power source type	DC, PoE
Power consumption (typical)	4 W

Power consumption (max)	9.2 W
-------------------------	-------

Power consumption (Power over Ethernet (PoE))	4.9 W
---	-------

DC output voltage	12
-------------------	----

Operational conditions

Operating temperature (T-T)	-30 - 60 °C
-----------------------------	-------------

Storage temperature (T-T)	-40 - 60 °C
---------------------------	-------------

Operating relative humidity (H-H)	0 - 95%
-----------------------------------	---------

System requirements

Mobile operating systems supported	Android, iOS
------------------------------------	--------------

Weight & dimensions

Height	122 mm
--------	--------

Diameter	9.4 cm
----------	--------

Weight	713 g
--------	-------

Packaging data

Package weight	986 g
----------------	-------

Packaging content

Number of cameras	1
-------------------	---

Matmenys ir svoris

Matmenys (I × P × A)	19,00cm × 19,00cm × 17,00cm
----------------------	-----------------------------

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Zhejiang Dahua Technology Co., Ltd

Bin'an Road, Binjiang District No.1187 & 1199,
310053 Hangzhou, CN
dahuasecurity.com

ATSAKINGAS ASMUO ES

Dahua Technology GmbH

Niederkasseler Lohweg 185, 40547 Düsseldorf,
DE
dahuasecurity.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt