

WRL CAMERA 3+3MP PT DOME/P3D-3F-PV-P DAHUA

Gamintojas: **DAHUA** · Modelis: **P3D-3F-PV-P-PRO** · EAN: **6939554980251** · Prekės kodas: **770831**



189,90 €

Kaina su PVM

Be PVM: **156,94 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

The Picoo Dual Series camera features both a fixed lens and PT lens, providing versatility for various surveillance needs. In low-light conditions, it leverages advanced WizColor technology to deliver crisp and vibrant images comparable to those captured in daylight. The camera supports both Wi-Fi and PoE connectivity options, ensuring flexible and stable network connections. Its dual lens system enables smart detection through advanced functions, such as AI human and vehicle detection, effectively minimizing false alarms. Moreover, with the assistance of the PT lens, it automatically tracks moving targets.

Summary: Dahua Technology P3D-3F-PV-P. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired & Wireless. Mounting type: Corner, Product colour: White, Form factor: Bulb. Angle of rotation: 180°, Vertical field of view (thermal module): 48°, Horizontal field of view (thermal module): 10589°. Sensor type: CMOS. Maximum resolution: 2304 x 1296 pixels, Total megapixels: 6 MP, Video compression formats: H.264, H.264H, H.264B, M-JPEG | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/Wireless-Series/NEW-Channel/Outdoor-Camera/Picoo-Series/P3D-3F-PV-P> | Type: IP security camera | Connectivity technology: Wired & Wireless | Placement supported: Indoor & outdoor | Day/night mode: Yes | Form factor: Bulb | Mounting type: Corner | Product colour: White | International Protection (IP) code: IP66 | Angle of rotation: 180 | Horizontal field of view (thermal module): 10589 | Vertical field of view (thermal module): 48 | Sensor type: CMOS | Number of lenses: 1 | Maximum aperture number: 1 | Night vision: Yes | Maximum resolution: 2304 x 1296 | Total megapixels: 6 | Video compression formats: H.264/H.264B/H.264H/M-JPEG | Bit rate: 512 kbps-4096 kbps | Audio formats supported: G.711 µ-law/G.711 A-law/G.726/PCM | Ethernet LAN: Yes | Wi-Fi: Yes | Wi-Fi standards: 802.11b/802.11g/Wi-Fi 4 (802.11n) | Channel bandwidth: 2400 | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Ethernet LAN (RJ-45) ports: 1 | Motion sensor: Yes | Management software: Smart PSS Lite; DSS; DMSS | Power source type: PoE | Power consumption (typical): 2.3 | Power consumption (max): 9.8 | Power consumption (Power over Ethernet (PoE)): 11.1 | Operating temperature (T-T): -30 - 50 | Operating relative humidity (H-H): 0 - 95 | Width: 119.1 |

Depth: 159.4 | Height: 210 | Weight: 585 | Number of cameras: 2 | Unit Calculated Weight: 1.08 | Product Net Weight: 0.585 | Unit Calculated Volume: 0.007192 | Units per Shipping Box: 12 | Unit Width: 18.7 | Units per Pallet: 0 | Shipping Box Height: 31 | Unit Depth: 23 | Unit Height: 13.6 | Name: WRL CAMERA 3+3MP PT DOME/P3D-3F-PV-P DAHUA | Model name: P3D-3F-PV-P

Techninė specifikacija

Matmenys ir svoris

Matmenys (l × p × A)

23,00cm × 19,00cm × 14,00cm