

LevelOne RJ45 to SC Fast Ethernet Industrial Media Converter, Single-Mode Fiber, 30km, -40°C to 75°C

Gamintojas: **LEVEL ONE** · Modelis: **IEC-4301** · EAN: **4015867188163** · Prekės kodas: **771387**



265,90 €

Kaina su PVM

Be PVM: **219,75 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 100 Mbit/s 30000 m
- ✓ Ethernet LAN (RJ-45) ports: 1
- ✓ Single-mode Fiber ports quantity: 1 SC
- ✓ Black



Aprašymas

LevelOne IEC-4301 is an industrial Fast Ethernet media converter with a mini size, rugged aluminium case which providing superb heat dissipation. This converter is designed to be mounted on an industrial standard DIN-rail, as well as on the wall, plus the clearly visible status LEDs provide simple monitoring of port link activity. It also features Link Fault Pass Through in order to alert remote location when link status changes.

- 10/100BaseT to 100Base-FX
- Rugged aluminium case design in a mini size form factor
- 18V-36VAC & 12V-60VDC with polarity protection
- Link Fault Pass through (LFP) function
- Supports switch and pure converter mode
- Surge & ESD protection
- Maximum noise & interference immunity

- 40°C to 75°C (-40°F to 167°F) operating temperature range
- DIN-Rail or panel mount installation

Techninė specifikacija

Network	
Maximum data transfer rate	100 Mbit/s
Converter input interface	10Base-T, 100Base-TX
Converter output interface	100Base-FX
Networking standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
Ethernet interface type	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Store-and-forward	Yes
Duplex system	Full, Half
Performance	
Maximum transfer distance	30000 m
Fiber mode structure	Single-mode
Features	
Internal	No
LED indicators	Activity, Link, Power
Product colour	Black
Housing material	Aluminium
Ports & interfaces	
Fiber optic connector	SC
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Input voltage	12 - 60 V
Power consumption (typical)	1.44 W
Weight & dimensions	
Width	59 mm
Depth	49 mm
Height	36 mm

Weight	90 g
Operational conditions	
Operating temperature (T-T)	-40 - 75 °C
Storage temperature (T-T)	-40 - 75 °C
Operating relative humidity (H-H)	5 - 95%
Packaging content	
Quick installation guide	Yes
Packaging data	
Package width	160 mm
Package depth	105 mm
Package height	65 mm
Package weight	260 g
Package type	Box
Certificates	
Compliance certificates	RoHS
Certification	FCC Part 15 Subpart B Class A CE EN 55022 Class A FCC Part 15 Subpart B Class A, CE EN 55022 Class A EN61000-4-2 (ESD) Level 3 EN61000-4-3 (RS) Level 2 EN61000-4-4 (EFT) Level 2 EN61000-4-5 (Surge) Level 2 EN61000-4-6 (CS) Level 2 EN 61000-4-8 (PFMF) Level 1 UL508 (Pending) EN 50121-4 (Pending) IEC 60068-2-27 IEC 60068-2-32 IEC 60068-2-6
Logistics data	
Country of origin	Taiwan
Harmonized System (HS) code	85176990

Gamintojo ir saugos informacija

GAMINTOJAS

LevelOne

ATSAKINGAS ASMUO ES

Digital Data Communications GmbH
Im Defdahl 10 F, 44141 Dortmund, DE
level1.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt