

APC Smart-UPS On-Line nepertraukiamo maitinimo resursai (UPS) Dviguba konversija (prisijungus) 5 kVA 4500 W 10 AC išvestis(ys / čių)

Gamintojas: **IBM** · Modelis: **SRT5KRMXLI-6W** · EAN: **8592978040864** · Prekės kodas: **771663**



7 063,90 €

Kaina su PVM

Be PVM: **5 837,93 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dviguba konversija (prisijungus)
- ✓ 5 kVA 4500 W
- ✓ Signalų forma: Sinusas
- ✓ 10 AC išvestis(ys / čių)
- ✓ Rūgštinis akumulatorius (VRLA)
- ✓ Stelažas Juoda





Aprašymas

This APC Smart-UPS is designed for IT professionals or network administrators to maintain business uptime and continuity. This 5kVA on-line 3U rackmount UPS provides pure sine wave power and extended runtime to support critical electronics during power disruptions. It comes with Hard Wire 3-wire (1P+N+E) input, 6x IEC 320 C13 and 4x IEC 320 C19 outlets, and 2x IEC jumper cables. The UPS has an embedded Network Management Card for UPS network-based monitoring and management. The UPS comes with PowerChute Network Shutdown that provides graceful shutdown of physical servers, virtual machines, and HCI clusters. It has an additional SmartSlot for optional accessory card such as Dry Contact I/O card. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. The UPS has a 6-year warranty and comes with a built-in lead-acid battery.

Techninė specifikacija

Features	
UPS topology	Double-conversion (Online)
Output power capacity	5 kVA
Output power	4500 W
Waveform	Sine
Input operation voltage (min)	160 V
Input operation voltage (max)	275 V
Input frequency	40 - 70 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency regulation	50/60 Hz
Surge energy rating	480 J
Efficiency	94.1%
Crest factor	3:1
Emergency Power Off (EPO)	Yes
Output voltage Total Harmonic Distortion (THD)	3%
Noise level	55 dB
Surge protection	Yes
Audible alarm(s)	Yes
Auto-restart	Yes
Ports & interfaces	
AC outlet types	C13 coupler, C19 coupler

Power plug	Hardwire
AC outlets quantity	10 AC outlet(s)
Number of output IEC jumpers	2
USB port	Yes
Serial interface	Yes
Serial interface type	RJ-45
SmartSlot	Yes
SmartConnect port	No

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	845 VAh
Typical backup time at full load	4 min
Typical backup time at half load	11.8 min
Battery life (max)	5 year(s)
Battery recharge time	1.5 h
Hot-swap battery	Yes
Automatic battery test	Yes
Cold start	Yes
Replacement battery cartridge	APCRBC140

Design

Form factor	Rackmount
Product colour	Black
Rack capacity	3U
Display type	LCD
International Protection (IP) code	IP20

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Compliance certificates	RoHS
-------------------------	------

Certification	REACH, CE, CE Mark, EAC, EN/IEC 62040-1, EN/IEC 62040-2, IRAM, NOM, VDE
Packaging content	
Rack mount kit	Yes
Management card included	Yes
Quick installation guide	Yes
Sustainability	
Sustainability certificates	ENERGY STAR
Weight & dimensions	
Width	432 mm
Depth	719 mm
Height	130 mm
Weight	54.4 kg
Packaging data	
Bracket	Yes
Temperature sensor	Yes
Warranty card	Yes
Package width	610 mm
Package depth	960 mm
Package height	330 mm
Package weight	66.9 kg
Logistics data	
Products per pallet	6 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	8408.59
Other features	
Packaging content	Web/SNMP Management Card

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS
Schneider Electric SE
rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR
se.com

PLATINTOJAS
MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 VILNIUS
info@shopro.lt