

StarTech.com ST124HDVW vaizdo signalo jungiklis HDMI

Gamintojas: **STARTECH.COM** · Modelis: **ST124HDVW** · EAN: **065030883603** · Prekės kodas: **771844**



1 226,90 €

Kaina su PVM

Be PVM: **1 013,97 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **2x2 HDMI VIDEO WALL CONTROLLER:** Hardware-based video wall processor can split & scale a 4K 60Hz (4096x2160) HDMI video input into 4x HDMI 1080p output signals to create a large image across 4 displays for digital signage; 7.1ch audio, HDCP 2.2/1.4
- ✓ **EASY SETUP:** The 2x2 video wall setup is pre-configured by default; HDMI video wall splitter w/ EDID emulation allows source video to be detected and properly split w/ the correct video format; Bezel compensation ensures accurate image display
- ✓ **SERIAL & IP CONTROL:** Features RS232 & Ethernet ports for input/output control & configuration features w/the Windows-only app, command line, Telnet/UDP; Various layouts: 2x2/1x1/1x4/mirror-duplication
- ✓ **MOUNT ANYWHERE:** Flexible environment/system setup with durable & ventilated metal housing; Built-in mounting brackets for wall/surface mount; Supports screw locking cables (HDMI & power); ESD protection
- ✓ **STARTECH.COM ADVANTAGE:** IT professionals choice for over 30 years; 4-screen video wall controller backed for 2-years by StarTech.com incl. free 24/5 North America based multi-lingual tech support



Aprašymas

4K Video Wall Splitter | HDMI 2.0 | 1 Input 4 Outputs | 2-Year Warranty

This video wall controller lets you connect your HDMI video source to multiple HDMI displays, with support for Ultra HD resolutions and 7.1 surround sound audio. You can use the controller as a video splitter to distribute the same HDMI signal to four displays or you can combine your video source across four displays to create a 2x2 video wall.

Supports True 4K at 60Hz

Not all 2x2 video wall matrix controllers are created equal. While some HDMI 1.4 video wall controllers can achieve 4K resolutions, they'll only work at a 30Hz refresh rate. This 4K 60Hz HDMI video wall processor offers full support for HDMI 2.0, including true 4K resolution at 60Hz.

Widely Compatible

The HDMI video wall splitter supports HDCP 2.2 and is backward compatible with 4K 30Hz and 1080p displays. This ensures that it will work with lower resolution displays such as TVs around your site or in your digital signage application.

Easy Installation and Setup

For hassle-free setup, the 4K HDMI splitter offers easy plug-and-play installation. Simply connect your source and 4 displays and the 4k video wall splitter will automatically create a video wall at the appropriate resolution.

The Choice of IT Pros Since 1985

StarTech.com conducts thorough compatibility and performance testing on all our products to ensure we are meeting or exceeding industry standards and providing high-quality products to IT Professionals. Our local StarTech.com Technical Advisors have broad product expertise and work directly with our StarTech.com Engineers to provide support for our customers both pre and post-sales.

The ST124HDVW is backed by a 2-year StarTech.com warranty and free lifetime technical support.

Techninė specifikacija

Ryšys	
Vaizdo priedo tipas	HDMI
HDMI versija	2.0
HDMI įvestis	1
HDMI išvesčių skaičius	4
USB priedo tipas	USB A tipo
RJ-45 įvesties priedai	1
RS-232 portai	1
DC įėjimo lizdas	Taip
Savybės	
Medžiaga	Metalas
Produkto spalva	Juoda

Išplėstiniai ekrano identifikacijos duomenys (EDID)	Taip
HDCP	Taip
Maksimalus atnaujinimo dažnis	60 Hz
Palaikomos grafikos rezoliucijos	4096 x 2160
LED indikatoriai	Taip
Garso išvesties kanalai	7.1 kanalai
HDCP versija	2.2
Energijos valdymas	
AC įėjimo įtampa	100 - 240 V
AC adapterio įėjimo srovė	1 A
AC adapterio išėjimo įtampa	24 V
AC adapterio išėjimo srovė	1,25 A
Sertifikatai	
Sertifikavimas	CE, FCC, REACH
Svoris ir matmenys	
Plotis	165 mm
Ilgis	230 mm
Aukštis	45 mm
Svoris	1 kg
Pakuotės duomenys	
Pakuotės plotis	263 mm
Pakuotės gylis	302 mm
Pakuotės aukštis	70 mm
Paketo svoris	1,6 kg
Pakuotės turinys	
Instrukcija	Taip
Kintamosios srovės adapteris	Taip
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-20 - 60 °C
Darbo santykinės drėgmės diapazonas	20 - 90%
Techninė informacija	
Atitikties sertifikatai	RoHS
Logistikos duomenys	

Darniosios sistemos (DS) kodas	85176990
Pagrindinės (išorinės) dėžės plotis	318 mm
Pagrindinės (išorinės) dėžės ilgis	550 mm
Pagrindinės (išorinės) dėžės aukštis	380 mm
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	10 vnt

Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA
startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt