

Dahua Technology IPC-HDW3649QM-S-IL-0280B security camera Turret IP security camera Indoor & outdoor 3288 x 1850 pixels Ceiling

Gamintojas: **DAHUA** · Modelis: **IPC-HDW3649QM-S-IL-0280B** · EAN: **6939554920219** · Prekės kodas: **771862**



331,90 €

Kaina su PVM

Be PVM: **274,30 €**

Sandėlyje



Prekė internetu

Nusenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 6-MP 1/2.7" CMOS image sensor, low luminance, and high definition image
- ✓ Outputs max. 8 MP (3840 × 2160)@25/30 fps
- ✓ H.265 codec, high compression rate, ultra-low bit rate
- ✓ Built-in multi-core light, the max. IR distance is 30 m and the max. warm light distance is 30 m
- ✓ ROI, SMART H.264+/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- ✓ Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- ✓ Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human), stay detection, loitering detection; face detection (full image)
- ✓ Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- ✓ Max. 512 G Micro SD card; built-in Mic
- ✓ 12 VDC/PoE power supply



Aprašymas

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

Techninė specifikacija

Performance	
Type	IP security camera
Placement supported	Indoor & outdoor
Connectivity technology	Wired
Wide Dynamic Range (WDR)	Yes
Day/night mode	Yes
Certification	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU
Design	
Mounting type	Ceiling
Product colour	White
Form factor	Turret
Housing material	Metal
Camera	
Rotating	Yes
White balance	Auto, Natural, Street lamp, Outdoor, Manual, Regional custom
Camera shutter type	Electronic
Camera shutter speed	1/3–1/100000
Number of Privacy masking areas	8
Image sensor	
Sensor type	CMOS
Number of sensors	1
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Progressive scan	Yes
Lens system	
Number of lenses	1
Zoom capability	No
Maximum aperture number	1.4

Fixed focal length	2.8 mm
Detect distance (wide)	84.8 m
Observe distance (wide)	33.9 m
Recognize distance (wide)	17 m
Identify distance (wide)	8.5 m
Closest focusing distance	1.4 m
Lens distortion correction (LDC)	Yes
Night vision	
Night vision	Yes
Video	
Maximum resolution	3288 x 1850 pixels
Total megapixels	6 MP
Video compression formats	H.265, H.264, H.264B, H.264H
Video streaming	Yes
Noise reduction	Yes
Noise reduction technology	3D noise reduction
Gain control type	Auto/Manual
Bit rate control	Variable Bit Rate (VBR), Constant Bit Rate (CBR), Adaptive Bit Rate (ABR)
Bit rate	3 kbps–16384 kbps
Back Light Compensation (BLC)	Yes
Highlight Compensation (HLC)	Yes
Region of Interest (ROI) encoding	Yes
Scene self-adaptation (SSA)	Yes
Audio	
Audio formats supported	PCM, G.711 A-law, G.726, G.723, G.711 μ -law
Built-in microphone	Yes
Number of microphones	1
Network	
Ethernet LAN	Yes
Wi-Fi	No
Bluetooth	No
Ethernet interface type	Fast Ethernet
Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP; P2P
Number of users	20 user(s)

Storage

Built-in HDD	No
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB
ROM capacity	256 MB
RAM capacity	1024 MB

Security

Video motion detection	Yes
Mirror	Yes
Motion detection system	SMD 4.0

Management features

Cloud-managed	Yes
Management software	Smart PSS Lite; DSS; DMSS; DoLynk Care

Power

Power source type	DC, PoE
Power consumption (typical)	3.7 W
Power consumption (max)	7.4 W
Power consumption (Power over Ethernet (PoE))	5.3 W
Power consumption (Power over Ethernet (PoE)) (max)	9.5 W
DC output voltage	12

Operational conditions

Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	122 mm
Depth	122 mm
Height	105.5 mm
Weight	530 g

Packaging data

Package weight	710 g
----------------	-------

Packaging content

Number of cameras

1

Matmenys ir svoris

Matmenys (I × P × A)

14,00cm × 15,00cm × 14,00cm

Dokumentai ir vaizdo įrašai[> Gaminio lankstinukas](#)**Gamintojo ir saugos informacija**

GAMINTOJAS

Zhejiang Dahua Technology Co., Ltd

Bin'an Road, Binjiang District No.1187 & 1199,
310053 Hangzhou, CN

dahuasecurity.com

ATSAKINGAS ASMUO ES

Dahua Technology GmbH

Niederkasseler Lohweg 185, 40547 Düsseldorf,
DE

dahuasecurity.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt