

Lindy 10m Fibre Optic Hybrid DP 2.0 UHBR10 Cable

Gamintojas: **LINDY** · Modelis: **38520** · EAN: **4002888385206** · Prekės kodas: **771895**



230,90 €

Kaina su PVM

Be PVM: **190,83 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Combines copper and fibre optic cable for a hybrid, long distance DisplayPort connectivity solution
- ✓ Supports resolutions up to 4K@144Hz, 8K@60Hz
- ✓ DP2.0 standard with UHBR10 support, 40Gbps bandwidth (4 lanes, 10Gbps per channel)
- ✓ Flexible and robust cable structure for any kind of installations
- ✓ 2-Year Warranty



Aprašymas

Lindy's range of Fibre Optic Hybrid cables are a professional solution for extending DP signals over longer distances. Combining the flexibility and high EMI and RFI resistance of fibre optic cable with standard copper cabling, these hybrid cables are ideal for use in critical AV setups, commercial displays or high-performance residential installations.

The internal technology provides uncompressed amplification of the DP signal, allowing long distance extension of DP 8K content that is simply not possible with passive cables.

With 40Gbps bandwidth (UHBR10), these cables support DisplayPort 2.0 resolutions up to 3840x2160@144Hz, and 7680x4320 / 10240x4320@60Hz. Content can be viewed with incredible detail and clarity at higher refresh rates and supporting static and dynamic HDR for optimum viewing of movies, graphics or imagery.

Techninė specifikacija

Features	
Cable length	10 m
Connector 1	DisplayPort
Connector 2	DisplayPort
Connector 1 gender	Male
Connector 2 gender	Male
Maximum resolution	7680 x 4320 pixels
Product colour	Black
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
DisplayPort version	2
Maximum refresh rate	144 Hz
Cable material	Fibre optic/Copper
Jacket material	Polyvinyl chloride (PVC)
Connector housing material	PVC
AWG wire size	24
Data transfer rate	40 Gbit/s
Cable type	Round cable
Operational conditions	
Operating temperature (T-T)	-10 - 60 °C
Storage temperature (T-T)	-20 - 70 °C
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, UKCA
Certification	California Proposition 65
Weight & dimensions	
Cable diameter	4 mm
Connector 1 dimensions (WxDxH)	19.8 x 47.8 x 12 mm
Packaging data	
Package type	Box
Logistics data	
Warranty period	2 year(s)

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Matmenys ir svoris

Svoris	0,40kg
--------	--------

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.

Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB

lindy.com

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH

Markircher Str. 22, 68229 Mannheim, DE

lindy.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt