

Dahua Technology PoE SG1006P Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Gamintojas: **DAHUA** · Modelis: **DH-SG1006P** · EAN: **6923172571441** · Prekės kodas: **771905**



44,90 €

Kaina su PVM

Be PVM: **37,11 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Intelligent PoE
- ✓ Hi-PoE 60W (orange port)
- ✓ Long distance PoE
- ✓ PoE watchdog
- ✓ All-gigabit PoE ports
- ✓ Wide working temperature

Aprašymas

DH-SG1006P is an unmanaged Desktop Switch with 4 × 10/100/1000 Mbps PoE Ports. It provides 4 × 10/100/1000 Mbps Ethernet ports and 2 × 10/100/1000 Mbps uplink ports. The product is equipped with two types of transmission modes (Extend Mode On/Extend Mode Off). It also supports PoE watchdog to avoid manually maintenance and device restart, which can realize the intelligent management and reduce the cost.

Intelligent PoE

Provides control over power consumption and offers real-time monitoring to ensure power supplies receive priority with important ports and to prevent malfunctions caused by changes in power consumption. Supports ultra wide power supplies and is able to adapt to IPC power fluctuations.

Hi-PoE 60W (Orange Port)

In addition to the IEEE802.3af and IEEE802.3at standards, orange port also supports a maximum power output of 60W for powering high- power devices.

PoE Watchdog

Adopts the innovative PoE Watchdog. PoE Watchdog can be switched on by dialing or turning on the WEB page switch. It enables the switch to automatically detect port status and restart failed ports to recover connection in case of IPC connection exception. This enables intelligent operation and maintenance management in its truest sense, effectively reducing manual maintenance costs.

Long Distance PoE

By dialing or enabling long-range transmission on the WEB interface, the transmission distance of a PoE port can be up to 250 m, meeting the requirements of wired transmission (bandwidth reduced to 10 Mbps).

8-pin Assignment PoE Power Supply

Supports 8-pin simultaneous power supply (1/2/4/5 positive, 3/6/7/8 negative). Signal lines and idle lines supply power at the same time. Compatibility with IPC is enhanced. Cable loss is reduced. Loading capacity is increased.

Techninė specifikacija

Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	6
Basic switching RJ-45 Ethernet ports type	Gigabit Ethernet (10/100/1000)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Gigabit Ethernet (copper) ports quantity	6
Uplink ports quantity	2
Network	
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
10G support	No
Flow control support	Yes
Data transmission	
MAC address table	2000 entries
Switching capacity	14 Gbit/s
Forwarding rate	8.928 Mpps
Packet buffer memory	1 MB
Design	
Product colour	Black
Wall mountable	Yes
Power	

Power source	DC/PoE
DC input voltage	48 - 57 V
Input voltage	57 V
Power consumption (max)	60 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet (PoE) ports quantity	4
Total Power over Ethernet (PoE) budget	60 W
Operational conditions	
Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	5 - 95%
Weight & dimensions	
Width	85 mm
Depth	130 mm
Height	26 mm
Weight	300 g

Dokumentai ir vaizdo įrašai

- › [Naudojimo instrukcija](#)
- › [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Zhejiang Dahua Technology Co., Ltd

Bin'an Road, Binjiang District No.1187 & 1199,
310053 Hangzhou, CN
dahuasecurity.com

ATSAKINGAS ASMUO ES

Dahua Technology GmbH

Niederkasseler Lohweg 185, 40547 Düsseldorf,
DE
dahuasecurity.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt