

# DELL PowerEdge T360 server 480 GB Tower (4.5U) Intel Xeon 6 6315P 2.8 GHz 16 GB DDR5-SDRAM 700 W

Gamintojas: **DELL** · Modelis: **EMEA\_PROMO\_T360\_SPL3** · EAN: **2000001387924** · Prekės kodas: **772666**



## 3 637,90 €

Kaina su PVM

Be PVM: **3 006,53 €**

**Sandėlyje**



**Prekė internetu**

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

## Pagrindinės savybės

- ✓ Intel Xeon 6 6315P 2.8 GHz
- ✓ 480 GB
- ✓ 16 GB DDR5-SDRAM
- ✓ Tower (4.5U) 700 W



## Aprašymas

DELL PowerEdge T360. Processor family: Intel Xeon 6, Processor frequency: 2.8 GHz, Processor model: 6315P. Internal memory: 16 GB, Internal memory type: DDR5-SDRAM. Total storage capacity: 480 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 700 W, Redundant power supply (RPS) support. Chassis type: Tower (4.5U)

## Techninė specifikacija

### Processor

|                        |              |
|------------------------|--------------|
| Processor family       | Intel Xeon 6 |
| Processor manufacturer | Intel        |
| Processor model        | 6315P        |

|                                            |                                   |
|--------------------------------------------|-----------------------------------|
| Processor frequency                        | 2.8 GHz                           |
| Processor boost frequency                  | 5.2 GHz                           |
| Performance cores                          | 4                                 |
| Processor cores                            | 4                                 |
| Processor cache                            | 12 MB                             |
| Thermal Design Power (TDP)                 | 55 W                              |
| Processor threads                          | 4                                 |
| Memory types supported by processor        | DDR5-SDRAM                        |
| Memory clock speeds supported by processor | 4800 MHz                          |
| Memory                                     |                                   |
| Internal memory                            | 16 GB                             |
| Internal memory type                       | DDR5-SDRAM                        |
| Maximum internal memory                    | 128 GB                            |
| Memory slots                               | 4x DIMM                           |
| ECC                                        | Yes                               |
| Storage                                    |                                   |
| Total storage capacity                     | 480 GB                            |
| RAID support                               | Yes                               |
| Optical drive type                         | No                                |
| Number of SSDs installed                   | 1                                 |
| SSD capacity                               | 480 GB                            |
| SSD interface                              | SATA III                          |
| SSD size                                   | 2.5"                              |
| Supported SSD sizes                        | 3.5"                              |
| Number of SSDs supported                   | 8                                 |
| Supported RAID controllers                 | AIC PERC 11, PERC H355 Adapter FH |
| Hot-Plug support                           | Yes                               |
| Drive writes per day (DWPD)                | 1                                 |
| Storage drive adapter included             | Yes                               |
| Storage drive adapter type                 | 2.5" - 3.5"                       |
| Network                                    |                                   |
| Ethernet LAN                               | Yes                               |
| Cabling technology                         | 10/100/1000Base-T(X)              |
| Ethernet interface type                    | Gigabit Ethernet                  |

**Ports & interfaces**

|                                                 |   |
|-------------------------------------------------|---|
| Ethernet LAN (RJ-45) ports                      | 2 |
| USB 2.0 ports quantity                          | 3 |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 4 |
| VGA (D-Sub) ports quantity                      | 1 |
| Serial ports quantity                           | 1 |
| Power cables quantity                           | 2 |

**Expansion slots**

|                      |   |
|----------------------|---|
| PCI Express x4 slots | 2 |
|----------------------|---|

**Design**

|                |              |
|----------------|--------------|
| Chassis type   | Tower (4.5U) |
| Product colour | Black        |

**Software**

|                              |                                                                                                                                     |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Operating system installed   | No                                                                                                                                  |
| Compatible operating systems | Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi |

**Power**

|                                              |             |
|----------------------------------------------|-------------|
| Redundant power supply (RPS) support         | Yes         |
| Power supply                                 | 700 W       |
| Number of redundant power supplies supported | 2           |
| Number of redundant power supplies installed | 2           |
| Power supply input voltage                   | 200 - 240 V |

**Operational conditions**

|                                 |             |
|---------------------------------|-------------|
| Storage temperature (T-T)       | -40 - 65 °C |
| Storage relative humidity (H-H) | 5 - 95%     |
| Operating altitude              | 0 - 2048 m  |
| Non-operating altitude          | 0 - 12000 m |

**Certificates**

|                       |                  |
|-----------------------|------------------|
| 80 PLUS certification | 80 PLUS Titanium |
|-----------------------|------------------|

**Carbon footprint**

|                                                         |        |
|---------------------------------------------------------|--------|
| Total carbon footprint (kg of CO2e)                     | 1409   |
| Total carbon emissions, standard deviation (kg of CO2e) | 1213   |
| Carbon emissions, manufacturing (kg of CO2e)            | 295.89 |
| Carbon emissions, logistics (kg of CO2e)                | 154.99 |

|                                             |                             |
|---------------------------------------------|-----------------------------|
| Carbon emissions, energy usage (kg of CO2e) | 929.94                      |
| Carbon emissions, end-of-life (kg of CO2e)  | 28.18                       |
| PAIA version                                | PAIA 1.4.0, 2024            |
| Weight & dimensions                         |                             |
| Width                                       | 175 mm                      |
| Depth                                       | 581.1 mm                    |
| Other features                              |                             |
| Data transfer rate                          | 6 Gbit/s                    |
| Bytes per sector                            | 512e                        |
| Target workload                             | Read Intensive (RI)         |
| Matmenys ir svoris                          |                             |
| Matmenys (I × P × A)                        | 55,00cm × 80,00cm × 39,00cm |
| Svoris                                      | 23,00kg                     |

Dokumentai ir vaizdo įrašai

> [Atitikties deklaracija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

DELL

ATSAKINGAS ASMUO ES

Dell B.V.

Transformatorweg 383, 1014 AK Amsterdam, NL  
[dell.com](https://dell.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius  
[info@shopro.lt](mailto:info@shopro.lt)

Saugos dokumentai

> [Atitikties deklaracija](#)