LevelOne 16-Port Fast Ethernet PoE Switch, 802.3at/af PoE, 500W

Gamintojas: **LEVELONE** · Modelis: **FEP-1612** · EAN: **4015867170137** · Prekės kodas: **773916**



735,90 €

Kaina su PVM

Be PVM: **608,18 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Unmanaged
- ✓ Basic switching RJ-45 Ethernet ports quantity: 16
- ✓ Cat5 10BASE-T, 100BASE-TX
- ✓ MAC address table: 4096 entries Switching capacity: 3.2 Gbit/s
- ✓ Rack mounting
- ✓ Power over Ethernet (PoE)






Aprašymas

LevelOne FEP-1612 features 16 10/100Mbps Fast Ethernet ports with IEEE 802.3at/af PoE interfaces. It supports MDI / MDI-X convertible on 16 10/100Mbps ports and provides PoE inject function on PoE ports which are able to IEEE 802.3af or 802.3at compliant powered devices remotely.

The FEP-1612 equipped with the MDI/MDI-X auto detection for easily plug and play connection, regardless of cabling types in straight through or crossover. It also provides a simple, cost-effective, and highly reliable network connection for data and power transmission. Furthermore, it is the ideal device for bridging among Ethernet, Fast Ethernet workgroups and networks. It fits all kind of Ethernet installations such as campus, workgroup, department, enterprise, telecom or industrial applications.

The FEP-1612 features non-blocking 3.2Gbps backplane that greatly simplifies the tasks of upgrading your LAN for catering to increase bandwidth demands.

- IEEE 802.3af/at PoE compliant to simplify deployment and installation

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

- Auto-detection and protection of non-standard PoE devices
- Supports 4K MAC address auto-learning and auto-aging
- 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- 19-inch metal housing
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
- Total PoE power budget: 480W, up to 30W per port

Techninė specifikacija

Management features	
Switch type	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	Fast Ethernet (10/100)
Installed SFP modules quantity	0
Installed SFP+ modules quantity	0
Network	
Networking standards	IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x
10G support	No
Copper ethernet cabling technology	10BASE-T, 100BASE-TX
Cable types supported	Cat5
Full duplex	Yes
Auto MDI/MDI-X	Yes
Auto-negotiation	Yes
Data transmission	
MAC address table	4096 entries
Switching capacity	3.2 Gbit/s
Store-and-forward	Yes
Packet forwarding rate (100 Mbps)	148000 pps
Packet forwarding rate (10 Mbps)	14880 pps
Design	
Rack mounting	Yes
Stackable	No
Product colour	Grey
LED indicators	Activity, LAN, PoE, Power
Performance	
Buffer size	160 KB

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	5 A
Power consumption (typical)	500 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	Yes
Power over Ethernet plus (PoE+) ports quantity	16
Total Power over Ethernet (PoE) budget	480 W
Operational conditions	
Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	200 mm
Depth	480 mm
Height	44 mm
Weight	2.85 kg
Packaging content	
Cables included	AC
Quick start guide	Yes
Packaging data	
Package width	260 mm
Package depth	535 mm
Package height	90 mm
Package weight	3.7 kg
Certificates	
Certification	FCC, CE
Logistics data	
Country of origin	Taiwan
Harmonized System (HS) code	85176990

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

LevelOne

ATSAKINGAS ASMUO ES

Digital Data Communications GmbH
Im Defdahl 10 F, 44141 Dortmund, DE
level1.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt