BenQ LU935 Standartinio nuotolio projektorius 6000 ANSI lumens DLP WUXGA (1920x1200) Balta

Gamintojas: **BENQ DEUTSCHLAND** · Modelis: **9H.JNN77.15E** · EAN: **4718755084591** · Prekės kodas: **774004**



2 985,90 €

Kaina su PVM

Be PVM: **2 467,69 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Verslui Standartinio nuotolio projektorius Balta
- ✓ DLP 6000 ANSI lumens
- ✓ Lazeris 20000 h
- ✓ WUXGA (1920x1200) 16:10 3000000:1
- ✓ Ekrano dydžio suderinamumas: 762 - 7620 mm (30 - 300") Spalvų skaičius: 1,07 milijardo spalvų
- ✓ Fokusas: Rankinis Priartinimo galimybė
- ✓ Ethernet LAN jungtis
- ✓ Įmontuoti garsiakalbiai 10 W
- ✓ AC 440 W











Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Aprašymas

Revolutionary Laser Technology

BenQ introduces a full line of innovative projectors featuring proprietary DLP high brightness laser technology.

Superior Bright

Zero-deviation alignment of laser diodes boosts luminous flux into the light tunnel, improving light efficacy.

Superior Performance

Dual synchronized color wheels utilize an additive yellow segment, stimulating precise RGBY spectra for optimal chromatic performance.

Superior Durability

Comprising over two million micromirrors that reflect pure light through the color wheel, the DLP chip is hermetically sealed to resist heat for over 200,000 hours without degradation.

High Quality Presentation
Advanced Modes for Supreme Presentation Quality
BenQ LU935’s color modes are designed to fit all modern corporate presentation needs.
Infographic Mode: Showcasing the text and graphics in detail due to high brightness and better color gradation through the 92% Rec.709 color coverage, ensuring more saturated and lively color performance.
Presentation Mode: Designed for conventional presentation with texts and charts, producing the truest blacks and exemplary image sharpness for unmatched readability.
Video Mode: Designed for preserving dynamic color details when playing videos in meeting room with ambient light.

Dual Color Wheels Produce 92% Rec.709 Color Coverage for Optimal Color Performance

LU935’s powerful laser projection utilizes a dual color wheel system to produce unparalleled color performance that achieves a 92% Rec.709 color coverage. By increasing color ratios and the purity of RGBY color, LU935 dramatically enhances color saturation to ensure superior presentation quality.

Laser-Enabled Ultra-High Contrast

LU935 Laser Projector creates strikingly clear images with stratospherically high contrast ratio of 3,000,000 for true deep blacks, vividly rich colors, and fine subtle details. LU935 also features spontaneous response, requiring no wait to turn on or resume from blanking in true black for flexible performance capability.

Easy Installation

Large H/ V Lens Shift Designed to Fit Various Placement

LU935’s large and H/V lens shift system can be used to properly align the image, shifting up to 60% vertically and 23% horizontally relative to the size of the screen, deliver perfectly proportioned images despite installation or placement challenges in any venue.

The 1.6x Zoom for Efficient Upgrades and Installation

With 1.6x Big Zoom, corporations can replace outdated projectors without repositioning existing ceiling mounts as well as place the new projector easily into any space to project large-scale images. The 1.6x zoom allows LU935 to be mounted anywhere from 3.5 to 5.6 meters from the screen and project images of 120", which is the typical image size for corporate meeting rooms, avoiding costly renovation or installation downtime.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

360° Rotation Projection

BenQ’s LU935 can be tilted vertically at any angle, allowing projection onto ceiling, walls, floors, or angled signage to fulfill presentation in corporate venues of any sizes.

Advanced Image Calibration for Ideal Projection Alignment

LU935 is equipped with a two-dimensional keystone correction range of ±30° on both horizontal and vertical axes to counteract the trapezoid effect, a common phenomenon when the projector must be installed off-center. Installers can use Corner Fit control to adjust each corner respectively, for perfectly aligned image geometry.

Display Resolution Switch for Multi Display Compatibility

Users can change the LU935 native resolution from WUXGA into 1080P through display resolution switch function. This helps to increase the compatibility with 16:9 screens while doing multi-display projection as well as fitting into the existing 16:9 projector screen while replacement. When the native resolution is set at 1080P, the digital lens shift function will be enabled and the whole lens shift range will be up to ±72% from ±62% vertically, and thus installer can fine-tune and aligned the images, significantly save more setup time.

Easy White Balance Adjustment Minimize Differences Between Projections

LU935 supports easy white balance adjustment in OSD, ensures images consistency for better viewing experience especially in multi-display conference room.

Wired Remote Control for Easy Operation

LU935’s wired remote control offers projector installers and IT managers extra set-up convenience and ease of operation. The added wired control functionality makes the device a dependable choice for projector installation adjustment. Installers and IT managers can assign a specific remote control ID to each projector, avoiding signal interference and unintentional changes when installing multiple projectors in a venue.

Low Maintenance

20,000 Hour Long-Lasting Performance

BenQ LU935 laser projectors deliver 20,000 hours of superior image quality and performance. The laser light source resists color decay over time, making BenQ laser projectors ideal for multiple projections without concern for adjacent projectors generating different levels of brightness after a period of operation.

Filter-Free DLP Technology for Lasting Vibrant Color

BenQ LU935 laser projector is based on the absolute reliability of the 1-chip DLP design. The highly durable DLP chip can last over 20,000 hours without degradation, ensuring true-to-life colors and pristinely legible text over countless uses. With filter-free DLP technology, LU935 reduces total cost of ownership and no time-consuming filter maintenance to worry about.

DustGuard Pro Technology for Severe Conditions

LU935 is designed with BenQ DustGuard Pro Technology, which sealed laser modules and enclosed light engines to protect the DMD chip, color wheel sensor, laser module, and other optical components. The design has passed the dust chamber test standard for the international dustproof rating of IP5X. It effectively eliminates color wheel sensor failure, visible spots on the image and color decay to significantly reduce service costs and downtime.

High System Integration & Compatibility

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

HDBaseT for Uncompressed Transmission and Control

LU935 is with groundbreaking HDBaseT connectivity combines video, audio, RS-232 and LAN signal control signals from multiple sources including: PCs, laptops, document cameras, Blu-ray and DVDs onto a single RJ-45 cable. This ensures seamless transmissions up to 100 meters.

Third Party Network / Web Control Compatibility

LU935 is widely compatible with leading projector control systems including Extron, Crestron and PJ-Link, which fulfills network control via LAN, making it simple to integrate into corporate network infrastructures. When there is no LAN infrastructure, LU935 also supports RS-232 for reliable long-distance Installations up to 15 meters.

BenQ DMS Local

For users who would like to control all their displays remotely via LAN, you can download and install the DMS Local software for your system. DMS Local is a Device Information and Management software for use in the Windows operating system. DMS Local also supports Agent Mode which allows you to integrate your DMS Local settings to the cloud-based DMS Cloud.

Techninė specifikacija

Prožektorius	
Projektoriaus ryškumas	6000 ANSI lumens
Projektavimo technologija	DLP
Projektoriaus natūrali rezoliucija	WUXGA (1920x1200)
Kontrasto santykis (tipinis)	3000000:1
Natūralus kraštinių santykis	16:10
Ekrano dydžio suderinamumas	762 - 7620 mm (30 - 300")
Kontrasto santykis (dinaminis)	3000000:1
Spalvų skaičius	1,07 milijardo spalvų
Horizontali diapazono riba	15 - 102 kHz
Vertikali diapazono riba	24 - 120 Hz
Pagrindo koregavimas, horizontalus	-30 - 30°
Pagrindo koregavimas, vertikalus	-30 - 30°
Matricos dydis	1,22 cm (0.48")
Šviesos šaltinis	
Šviesos šaltinio tipas	Lazeris
Šviesos šaltinio naudingo tarnavimo trukmė	20000 h
Lęšių sistema	
Fokusas	Rankinis
Diafragmos intervalas	1,83 - 1,86
Priartinimo galimybė	Taip

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Priartinimo santykis	1.6:1
Rodymo santykis	1.36 - 2.18
Horizontalaus objektyvo poslinkio diapazonas	-23 - 23%
Vertikalaus lęšio poslinkio diapazonas	-60 - 60%

Video

Analoginio signalo formato sistema	NTSC, PAL, SECAM
Pilnas HD	Taip
Palaikomos grafikos rezoliucijos	640 x 480 (VGA)
Palaikomi vaizdo režimai	480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Ryšys

VGA (D-Sub) portų kiekis	2
HDMI portų kiekis	2
Kompozuoti video in	0
Komponento video (YPbPr/YCbCr) in	0
DVI prievadas	Ne
Garso (kairė, dešinė) įvestis	0
Nuosekliosios sąsajos tipas	RS-232
HDMI jungties tipas	Viso dydžio
„HDBaseT“ prievadas	Taip
USB 2.0 portų kiekis	1
PC garso „in“ jungtis	Taip
PC garso „out jungtis“	Taip
AC (įtampa) įėjimas	Taip

Tinklas

Smart TV	Ne
Ethernet LAN jungtis	Taip
„Wi-Fi“	Ne
Ethernet LAN (RJ-45) portų kiekis	1

Laikmenos

Integruotas kortelių skaitytuvas	Ne

Savybės

Interaktyvus	Ne
HDCP	Taip
Virtualusis ekranas (OSD)	Taip

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Kilmės šalis	Kinija
Multimedija	
Įmontuoti garsiakalbiai	Taip
RMS galingumas	10 W
Konstrukcija	
Gaminio tipas	Standartinio nuotolio projektorius
Pozicija rinkoje	Verslui
Produkto spalva	Balta
Kabelio spynos lizdas	Taip
Laido spynos lizdo tipas	Kensington
Ekranas	
Įmontuotas ekranas	Ne
Energijos valdymas	
Maitinimo šaltinis	AC
Energijos suvartojimas	440 W
Energijos suvartojimas (laukimo režimu)	0,5 W
AC įėjimo įtampa	100 - 240 V
AC įėjimo dažnis	50 - 60 Hz
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Svoris ir matmenys	
Svoris	7 kg
Plotis	416 mm
Ilgis	351 mm
Aukštis	166 mm
Pakuotės plotis	470 mm
Pakuotės gylis	530 mm
Pakuotės aukštis	297 mm
Paketo svoris	9,2 kg
Pakuotės turinys	
Pridedamas nuotolinio valdymo pultelis	Taip
Pridėti kabeliai	AC
Logistikos duomenys	
Darniosios sistemos (DS) kodas	85286200

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Matmenys ir svoris	
Matmenys (I × P × A)	53,00cm × 47,00cm × 28,00cm

Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

Gamintojo ir saugos informacija

GAMINTOJAS

BenQ
Jihu Road Neihu 16, 114 Taipei, TW
benq.com

ATSAKINGAS ASMUO ES

BenQ Deutschland GmbH
Essener Straße 5, 46047 Oberhausen, DE
benq.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt