

StarTech.com 10G5A2CS-USB-C-HUB sąsajos šakotuvas USB 3.2 Gen 2 (3.1 Gen 2) Type-C 10000 Mbit/ai Sidabras

Gamintojas: **STARTECH** · Modelis: **10G5A2CS-USB-C-HUB** · EAN: **065030899086** · Prekės kodas: **776890**



152,90 €

Kaina su PVM

Be PVM: **126,36 €**

Sandėlyje





Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Priimančioji sąsaja: USB 3.2 Gen 2 (3.1 Gen 2) Type-C
- ✓ 10000 Mbit/ai
- ✓ Lizdo sąsajos: USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-C
- ✓ Sidabras
- ✓ Portų kiekis: 7





Aprašymas

Add 5x USB-A and 2x USB-C ports to a USB-C enabled Desktop/Laptop

Add seven USB 3.2 Gen 2 (10Gbps) ports (5x USB-A, 2x USB-C) to a USB-C computer using this 7-Port USB-C Hub. The USB Hub is self-powered with an included power adapter. The USB Hub features Overcurrent Protection (OCP). OCP aids in preventing peripherals from overdrawing power, avoiding USB device dropouts, and the computers from shutting down unexpectedly. Support for Wake On USB enables USB communications, from devices connected to the hub, to take the computer out of standby or other power saving/sleep modes.

High Performance USB 3.2 Gen 2 (10Gbps) Hub

The USB Hub shares 10Gbps from the USB host device, enabling high-speed data transfers for high-performance applications. The USB hub is backward compatible with previous USB versions, including USB 3.2 Gen 1 (5Gbps), USB 2.0 (480Mbps), and USB 1.1 (12Mbps). It features five USB-A ports and two USB-C ports. This combination of ports enables support for a wide range of modern and legacy USB devices, such as external storage devices (e.g., thumb drives, HDDs/SSDs), HD Cameras (e.g., webcams), mice, keyboards, and USB headsets.

Power and Charge USB Devices

The USB hub is self-powered, using the 65W power adapter. The hub features two USB BC 1.2 ports (1x USB-A, 1x USB-C), each providing 2.4A (12W) of power simultaneously, making it ideal to charge battery powered USB devices like smartphones, and tablets, while also providing a data connection. These ports will provide power with or without a host computer connected, with support for both CDP (Charging Downstream Port) & DCP (Dedicated Charging Port) applications. The hub features four USB-A, and one USB-C port that each provide the USB 3.2 standard of 0.9A (4.5W) of power. The included power adapter ensures that all ports will always provide specified power regardless of how many devices are connected.

USB-IF Certified Host Cable

A high-quality USB-IF certified USB-C host cable is included. The cable features a screw-locking, connector to ensure a secure and reliable connection to the USB hub. The Thermoplastic Elastomer (TPE) cable jacket is softer and more flexible than PVC jacketed cables.

Plug-and-Play Installation

The 7-Port USB Hub is OS independent supporting all operating systems, including Windows, macOS, ChromeOS, iPadOS and Android. Installation is automatic upon connection to a host computer.

Mount the USB Hub to a wall, desk, or VESA mount, using StarTech.com hub mounts: SSPMSVESA or SSPMSUDWM.

Enhance Productivity and Device Management with the StarTech.com Connectivity Tools Application

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that is compatible with a wide variety of IT connectivity accessories. The applicable software for this product is the USB Event Monitoring Utility. Use this utility to track and log any connected USB devices.

For more information and to download the StarTech.com Connectivity Tools application, please visit: www.StarTech.com/connectivity-tools

This product is backed for 2-years by StarTech.com, including free lifetime 24/5 multi-lingual technical assistance.

Techninė specifikacija

Ryšys	
Portų kiekis	7
Priimančioji sąsaja	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
Lizdo sąsajos	USB 3.2 Gen 2 (3.1 Gen 2) Type-A, USB 3.2 Gen 2 (3.1 Gen 2) Type-C
USB 3.2 2 kart. (3.1 2 kart.) A tipo prievadų skaičius	5
USB 3.2 2 kart. (3.1 2 kart.) C tipo prievadų skaičius	2
DC įėjimo lizdas	Taip
Savybės	
Duomenų perdavimo sparta	10000 Mbit/ai
Produkto spalva	Sidabras
LED indikatoriai	Būsena
Laido dangos medžiaga	Termoplastinis elastomeras (TPE)
Kabelio ilgis	1 m
Tinklas	
UASP palaikymas	Taip
Energijos valdymas	
Maitinimo tipas	DC
Energijos suvartojimas	65 W
Įėjimo įtampa	100 - 240 V
Išėjimo įtampa	19 V
Išėjimo srovė	3,42 A
Kištuko tipas	M tipas
Svoris ir matmenys	
Plotis	80 mm
Ilgis	115 mm
Aukštis	30 mm
Svoris	287 g
Pakuotės duomenys	
Pakuotės plotis	252 mm
Pakuotės gylis	175 mm
Pakuotės aukštis	96 mm
Paketo svoris	287 g

Pakuotės turinys	
Kintamosios srovės adapteris	Taip
Pridedamos maitinimo šakutės tipai	EU, UK, US
Pridėti kabeliai	Iš C tipo USB į C tipo USB
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 50 °C
Sandėliavimo temperatūros norma (T-T)	-20 - 70 °C
Darbo santykinės drėgmės diapazonas	0 - 95%
Logistikos duomenys	
Pagrindinės (išorinės) dėžės plotis	404 mm
Pagrindinės (išorinės) dėžės ilgis	284 mm
Pagrindinės (išorinės) dėžės aukštis	521 mm
Gaminių skaičius pagrindinėje (išorinėje) dėžėje	10 vnt
Techninė informacija	
Atitikties sertifikatai	CE, RoHS
Kitos savybės	
Lustų rinkinys	VIA - VL822-Q7, VIA - VL162
Tvarumas	
Tvarumo reikalavimų laikymasis	Taip
Matmenys ir svoris	
Matmenys (I × P × A)	25,00cm × 18,00cm × 10,00cm
Svoris	1,19kg

Dokumentai ir vaizdo įrašai

- > [Gaminio lankstinukas](#)
- > [Vaizdo įrašas](#) youtube.com/watch?v=rufzNk3ERrU

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London, CA

[startech.com](#)

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
[startech.com](#)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
[info@shopro.lt](#)