

D-Link 18-Port 2.5G Multi-Gigabit Smart Managed Switch with 2 x 10G SFP+ Ports

Gamintojas: **D-LINK** · Modelis: **DMS-1250-18/E** · EAN: **790069476648** · Prekės kodas: **777106**



417,90 €

Kaina su PVM

Be PVM: **345,37 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 16 Ports 2.5GE for downlink
- ✓ 2 Ports 10G SFP+ for uplink
- ✓ 6kV surge protection on all 2.5G ethernet ports
- ✓ Support LACP 802.3ad Link Aggregation
- ✓ Support Static Routing
- ✓ Support Loopback Detection
- ✓ Support Spanning Tree Protocol(STP/RSTP/MSTP)
- ✓ AAA support for RADIUS/TACACS+
- ✓ Support D-Link Safeguard Engine
- ✓ Manage through the Nuclias Network Controller



Aprašymas

The DMS-1250 Series is D-Link's newest family of Multi-Gigabit Ethernet smart switches. It provides multi-Gigabit connectivity, Power over Ethernet (PoE) capability, multiple management interfaces and advanced layer 2 features. The DMS-1250 Series provides a high-performance solution to expand your network and adapts to your business needs.

Highlights

Multi-Gigabit Ethernet Connection Delivers fast 2.5 Gbps performance using existing cabling, suitable for Wi-Fi 6 network deployments

10G Uplink Connections

Two 10-Gigabit Ethernet or SFP+ uplink ports allow for additional connections to a storage device or uplink network

Power over Ethernet

PoE+ (30W) or PoE++ (90W) options to simultaneously power multiple types of PoE devices with various power draw requirements

Techninė specifikacija

Management features	
Switch type	Managed
Switch layer	L2
Quality of Service (QoS) support	Yes
Web-based management	Yes
Traffic classification	Yes
ARP inspection	Yes
Configuring Location Settings (CLI)	Yes
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity	16
Basic switching RJ-45 Ethernet ports type	2.5G Ethernet (100/1000/2500)
SFP+ module slots quantity	2
Power connector	AC-in jack
Network	
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3z
Port mirroring	Yes
Flow control support	Yes
Link aggregation	Yes
Broadcast storm control	Yes
Rate limiting	Yes
Auto MDI/MDI-X	Yes
Spanning tree protocol	Yes
Active link detection	Yes
VLAN support	Yes
Number of VLANs	4096
Data transmission	
MAC address table	16000 entries

Switching capacity	120 Gbit/s
Forwarding rate	89.29 Mpps
Store-and-forward	Yes
Jumbo frames support	Yes
Jumbo frames	12000
Packet buffer memory	12 MB
Security	
DHCP features	DHCP server, DHCP snooping
Access Control List (ACL)	Yes
IGMP snooping	Yes
MAC address filtering	Yes
Loop protection	Yes
Password protection	Yes
Multicast features	
Multicast support	Yes
Design	
Rack mounting	Yes
Stackable	Yes
Product colour	Black
LED indicators	Yes
Performance	
Internal memory	512 MB
Flash memory	32 MB
Fanless	Yes
Power	
Power source	AC
Power supply included	Yes
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	22 W
Power over Ethernet (PoE)	
Power over Ethernet (PoE)	No
Operational conditions	
Operating temperature (T-T)	-5 - 50 °C

Storage temperature (T-T)	-20 - 70 °C
---------------------------	-------------

Operating relative humidity (H-H)	0 - 95%
-----------------------------------	---------

Storage relative humidity (H-H)	0 - 95%
---------------------------------	---------

Weight & dimensions

Width	440 mm
-------	--------

Depth	250 mm
-------	--------

Height	44 mm
--------	-------

Weight	2.97 kg
--------	---------

Matmenys ir svoris

Svoris	4,80kg
--------	--------

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

D-Link

ATSAKINGAS ASMUO ES

D-Link Benelux

Postbus 48, 5480 AA Schijndel, NL
dlink.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt