

Ubiquiti UniFi Pro HD 24 Managed L2/L3 2.5G Ethernet (100/1000/2500) 1U Grey

Gamintojas: **UBIQUITI** · Modelis: **USW-Pro-HD-24** · EAN: **810084696637** · Prekės kodas: **777477**



688,90 €

Kaina su PVM

Be PVM: **569,34 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: Industry Canada (IC) | Compliance certificates: CE | Reset button: Yes | Networking standards: IEEE 802.1x | Power over Ethernet (PoE): No | Product colour: Grey | Width: 442.4 mm | IGMP snooping: Yes | Rack mounting: Yes | AC input frequency: 50/60 Hz | Redundant power supply (RPS) support: Yes | Housing material: SGCC | AC input voltage: 100 - 240 V | LED indicators: Link | LED indicators: Status | Rate limiting: Yes | Weight: 4.2 kg | Port mirroring: Yes | MAC address table: 32000 entries | LED indicators: Speed | Flow control support: Yes | Switch layer: L2/L3 | Switching capacity: 230 Gbit/s | Power connector: AC/DC | DHCP features: DHCP server | DHCP features: DHCP guarding | Cables included: Power | Height: 44 mm | Throughput: 115 Gbit/s | Stackable: Yes | Heat dissipation: 102.36 BTU/h | SFP+ module slots quantity: 4 | Switch type: Managed | Power source: AC/DC | Form factor: 1U | Loop protection: Yes | Packet buffer memory: 2 MB | DHCP features: DHCP relay | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | 10G support: Yes | Forwarding rate: 171.12 Mpps | Operating relative humidity (H-H): 10 - 90% | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 22 | Quality of Service (QoS) support: Yes | Depth: 285 mm | Static route: Yes | Virtual LAN features: Voice VLAN | Multicast support: Yes | Operating temperature (T-T): -5 - 40 °C | Power supply included: Yes | Number of VLANs: 1000 | Rack mount kit: Yes | Power consumption (max): 60 W | DHCP

features: DHCP snooping | Display type: LCM | Broadcast storm control: Yes | Jumbo frames support: Yes | 10G Ethernet (copper) ports quantity: 2 | 2.5G Ethernet (copper) ports quantity: 22 | IPv4 routes: 12000

Techninė specifikacija

Matmenys ir svoris	
Matmenys (I × P × A)	12,00cm × 40,00cm × 52,00cm
Svoris	5,80kg