

Hikvision DS-7608NXI-K2/VPro 8-Channel NVR AcuSeek

Gamintojas: **HIKVISION** · Modelis: **DS-7608NXI-K2/VPro** · EAN: **6936422185985** · Prekės kodas: **778112**

332,90 €

Kaina su PVM

Be PVM: **275,12 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Aprašymas

ADVANCED SURVEILLANCE WITH ACUSEEK TECHNOLOGY

The Hikvision 8-ch 1U AcuSeek K VPro NVR is designed to elevate security monitoring with its innovative AcuSeek and AcuSearch functionalities. Utilizing Hikvision's AcuSense technology, this NVR minimizes manual oversight and reduces security costs by accurately identifying threats and minimizing false alarms. With the ability to connect and configure up to 8 IP cameras automatically, it streamlines the setup process, ensuring that users can focus on what matters most—effective surveillance.

IMPRESSIVE DECODING CAPACITY FOR HIGH-RESOLUTION VIDEO

This NVR supports a remarkable decoding capacity, accommodating up to 8 channels at various resolutions. It can handle 4 channels at 12 MP, 6 channels at 8 MP, or 8 channels at 4 MP, ensuring that users can capture high-definition video without compromising performance. The device supports multiple video formats, including H.265+/H.265/H.264+/H.264, allowing for efficient storage and transmission of video data while maintaining exceptional quality.

ROBUST AI FEATURES FOR ENHANCED SECURITY

Equipped with advanced AI capabilities, the Hikvision NVR excels in facial recognition, perimeter protection, and motion detection 2.0. It can model up to 50,000 targets per day, significantly enhancing the ability to monitor and analyze security footage. The integration of AI not only improves the accuracy of threat detection but also reduces the likelihood of false alarms, making it an invaluable tool for any security operation.

FLEXIBLE CONNECTIVITY AND HIGH BANDWIDTH PERFORMANCE

With an incoming bandwidth of 80 Mbps and an outgoing bandwidth of 160 Mbps, this NVR ensures seamless video streaming and playback. It supports a variety of network protocols, including TCP/IP and DHCP, allowing for easy integration into existing systems. The NVR features multiple output options, including HDMI and VGA, providing flexibility in how video is displayed and managed across different environments.

DURABLE DESIGN WITH EXTENSIVE STORAGE CAPACITY

The Hikvision 8-ch NVR is built to withstand a range of environmental conditions, operating effectively in temperatures from -10 °C to 55 °C (14 °F to 131 °F) and humidity levels of 10 to 90%. It supports up to 16 TB of storage per HDD across two SATA interfaces, ensuring ample space for extensive video recordings. With a compact design and lightweight construction, this NVR is ideal for various installation scenarios, making it a versatile choice for modern security needs.