# Zyxel GS1100-16 Ne-valdomas Gigabit Ethernet (10/100/1000) Juoda

Gamintojas: **ZYXEL** · Modelis: **GS1100-16E-EU0101F** · EAN: **4718937571376** · Prekės kodas: **778417**




**77,90 €**

Kaina su PVM

Be PVM: **64,38 €**

**Sandėlyje**

**Prekė internetu**
Nuskenuokite kodą arba apsilankykite www.shopro.lt

## Pagrindinės savybės

- ✓ Ne-valdomas
- ✓ Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 16
- ✓ Adreso lentelės dydis: 8000 įrašai Perjungimo pajėgumas: 32 Gbit/s


















## Aprašymas

- Non-blocking, wire-speed transmission
- Auto MDI/MDI-X support
- IEEE 802.3az compliant
- Fanless design for silent operation

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

- IEEE 802.3x flow control supported
- IEEE 802.1p CoS supported
- Jumbo frame support up to 10 K bytes (GS1100-24/24E)
- IEEE 802.3at PoE Plus standard with 30 W per port (GS1100-8HP)

## Affordable Solution for Gigabit Connections to the Desktop

The ZyXEL GS1100 Series is the best solution for instant Gigabit connectivity in office environments demanding silent operation and better energy efficiency. With power-saving functions, Gigabit Ethernet and a fanless design, the GS1100 Series provides plug-and-play simplicity for high-bandwidth network applications.

The ZyXEL GS1100 Series consists of four unmanaged switches: the GS1100-8HP, GS1100-16, GS1100-24 and GS1100-24E. The GS1100-16 and GS1100-24E feature 16 and 24 GbE ports. The GS1100-24 is a 24-port Gigabit switch with 2 additional open Gigabit SFP slots, while the GS1100-8HP is an 8-port Gigabit switch that complies with the IEEE 802.3at Power over Ethernet (PoE) Plus standard, providing 4 PoE ports with up to 30 watts per port.

## Green networking

The GS1100 Series not only offers Gigabit Ethernet connectivity for next-generation network applications, but also power-saving functions for better energy efficiency. Capable of dynamically adjusting power output according to traffic, active links and cable length, the GS1100 Series can reduce energy consumption for lowered operating costs.

## - Traffic detection — Energy Efficient Ethernet (EEE) compliance

The IEEE 802.3az Energy Efficient Ethernet (EEE) feature automatically detects network traffic and adjusts power consumption dynamically, enabling the switch to reduce power consumption during low link utilization periods. The GS1100 Series comes with IEEE 802.3az on/off button to help reduce power consumption. This button allows users to keep the best performance without transmit impacted or to have green support of Energy Efficient Ethernet mode with a simple push of a button.
- Inactive link detection
The inactive link detection function automatically reduces power usage when inactive links or devices are detected. The ZyXEL GS1100 Series can adjust power consumption according to link status and the number of active network devices.
- Cable length detection
This green feature enables the switch to automatically detect the length of connected Ethernet cables and adjust power usage accordingly. The shorter the cable length, the less power it consumes.

## Fanless design

The complete GS1100 Series comes in a fanless design that ensures silent operation in small or quiet office environments. The GS1100-8HP PoE model is specifically designed with an external power adapter that eliminates the need for an additional fan to cool down the device, making it perfect for quiet PoE deployments.

## Gigabit to the desktop

The ZyXEL GS1100 Series offers small offices 8/16/24-port Gigabit connectivity at the most competitive price. Additionally, the GS1100-24 model is equipped with 2 extra SFP slots, supported dual rate (100 M and GbE speed) that enable fiber optic connections for long-distance deployments. With Gigabit network performance and high cost-effectiveness, the GS1100 Series is the ideal solution for bandwidth-intensive applications such as high-resolution photo transmission, video/audio streaming and server farm connections.

## Freedom of installation via PoE (GS1100-8HP)

The GS1100-8HP supports the IEEE 802.3at PoE Plus standard to ease the installation of network devices in challenging spaces such as ceilings or walls. The power supply of up to 30 watts per port allows the GS1100-8HP to power PoE-enabled WLAN APs, VoIP phones and IP surveillance cameras through CAT-5 cables of less than 100 meters (300 feet) in length. With the ZyXEL GS1100-8HP, there is no need for extra power adapters in

installing PoE devices in difficult locations. This feature helps enterprises reduce installation time and cost when there are many such devices on the network.

## Techninė specifikacija

| | |
|---|---|
| **Valdymo funkcijos** | |
| Perjungimo tipas | Ne-valdomas |
| **Ryšys** | |
| Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius | 16 |
| Pagrindinių perjungimo RJ-45 eterneto prievadų tipas | Gigabit Ethernet (10/100/1000) |
| **Tinklas** | |
| Tinklo standartai | IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x |
| 10G parama | Ne |
| Transliacijos audros valdymas | Taip |
| Auto MDI/MDI-X | Taip |
| **Duomenų perdavimas** | |
| Adreso lentelės dydis | 8000 įrašai |
| Perjungimo pajėgumas | 32 Gbit/s |
| Paketo buferio atmintis | 0,256 MB |
| **Saugumas** | |
| MAC adresų filtravimas | Taip |
| **Konstrukcija** | |
| Produkto spalva | Juoda |
| LED indikatoriai | Taip |
| Saugumas | UL 60950-1, CSA 60950-1, EN 60950-1, IEC 60950-1, EU RoHS compliant |
| **Energijos valdymas** | |
| AC įėjimo įtampa | 100 - 240 V |
| AC įėjimo dažnis | 50 - 60 Hz |
| Energijos suvartojimas | 6,4 W |
| **„Power over Ethernet“ (PoE)** | |
| Maitinimas per Eternetą (PoE) | Ne |
| **Aplinkos sąlygos** | |
| Darbo temperatūros diapazonas (TT) | 0 - 50 °C |
| Sandėliavimo temperatūros norma (T-T) | -40 - 70 °C |
| Darbo santykinės drėgmės diapazonas | 10 - 95% |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

| | |
|---|---|
| **Svoris ir matmenys** | |
| Plotis | 215 mm |
| Ilgis | 133 mm |
| Aukštis | 42 mm |
| Svoris | 1 kg |
| **Pakuotės turinys** | |
| Instrukcija | Taip |
| **Sertifikatai** | |
| Sertifikavimas | CE, FCC, C-Tick, Class A (GS1100-8HP/24) CE, FCC, C-Tick, Class B (GS1100-16, 24E) BSMI CNS13438 |
| **Matmenys ir svoris** | |
| Matmenys (I × P × A) | 30,00cm × 12,00cm × 9,00cm |

## Dokumentai ir vaizdo įrašai

› Naudojimo instrukcija

## Gamintojo ir saugos informacija

GAMINTOJAS

**Zyxel Networks Corporation**
Industry East RD. IX, Hsinchu Science Park 2, 30076 Hsinchu, TW
zyxel.com

ATSAKINGAS ASMUO ES

**Zyxel Networks A/S**
Adenauerstraße 20/A3, 52146 Würselen, DE
zyxel.com

PLATINTOJAS

**MB KOMPIUTERIŲ GURU**
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt