

Bosch GCL 2-50 C Line/Point level 20 m 650 nm (<1 mW)

Gamintojas: **BOSCH** · Modelis: **0601066G00** · EAN: **3165140865579** · Prekės kodas: **784346**



171,90 €

Kaina su PVM

Be PVM: **142,07 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line/Point level
- ✓ Tripod thread: 1/4"
- ✓ IP54
- ✓ Maximum range: 20 m
- ✓ Levelling accuracy ($\pm$): 0.3 mm/m
- ✓ Self-levelling range ($\pm$): 4°
- ✓ Lithium-Ion (Li-Ion)
- ✓ Black, Blue

Aprašymas

Product highlights

Smart functions for maximum productivity

- Horizontal and vertical laser lines and two centred plumb points with optimal visibility
- Versatile to use with rotating multifunctional mount for a variety of mounting possibilities
- High visibility of the laser lines with a working range of 20 m (without receiver)
- Working range of 50 m with the LR 6 or LR 7 Professional receiver (optional)
- Pendulum lock ensures safe transport
- Bluetooth connection to Smartphone for remote control and adjustment of the tool
- Dual Power Source: Can be operated both with 12 V-Li-ion battery and with standard alkaline batteries
- Precise positioning of the laser lines around the plumb points – motorized positioning with RM 3 Professional (optional), using an app or remote control or manual positioning with RM 2 Professional

Scope of delivery

- 4 x 1.5 V LR6 (AA) batteries
- AA1 alkaline battery adapter
- GCL 2-50 C/CG Inlay 1

- Laser target plate
- Protective bag
- Rotating mount RM2

Techninė specifikacija

Features	
Maximum range	20 m
Levelling accuracy (±)	0.3 mm/m
Self-levelling range (±)	4°
Maximum range (with receiver)	50 m
Number of laser lines	2
Number of laser points	2
Colour of laser beam	Red
Laser class	2
Laser diode	650 nm (<1 mW)
Design	
Type	Line/Point level
Product colour	Black, Blue
Tripod mounting supported	Yes
Tripod thread	1/4"
International Protection (IP) code	IP54
Battery	
Operating time	70 h
Battery technology	Lithium-Ion (Li-Ion)
Battery voltage	12 V
Number of batteries supported	4
Operational conditions	
Operating temperature (T-T)	-10 - 50 °C
Storage temperature (T-T)	-20 - 70 °C
Weight & dimensions	
Depth	136 mm
Height	122 mm
Weight	600 g
Matmenys ir svoris	
Svoris	1,65kg

Gamintojo ir saugos informacija

GAMINTOJAS

Bosch

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt