



Access Point MIKROTIK 867 Mbps 2x10Base- T 100Base-TX 1000Base-T RBCAPGI- 5ACD2ND-XL

Modelis: RBCAPGI-5ACD2ND-XL

Gamintojas: MIKROTIK

EAN: 4752224007278

Prekės kodas: 79175

89.00€

cAP XL ac

The ceiling AP on steroids! Our bestseller cAP is back – juiced up and stronger than ever. Compared to the previous cAP models, the improved high-gain antenna increases the covered area by up to 100%!

Need a nice-looking access point that won't get in your way? Or perhaps you're managing the network in a crowded place and don't want everyone to have physical access to the device? Either way – ceiling is the answer! The device itself is pretty sleek - the low profile attracts less attention

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

than a smoke detector. Your clients, guests, or colleagues won't even notice it. But they will definitely notice the blazing fast wireless connection all across the premises.

The new design features a larger high-gain antenna, higher sensitivity, and a built-in reflector. These improvements allow increasing the covered area by up to 100%, compared to the previous cAP models!

The dual-band, dual-chain 2.4 and 5 GHz wireless radio provides a strong coverage in 360 degrees around it, so you don't have to worry about the placement of the device so much. Putting it on the ceiling eliminates many signal absorption problems, such as the signal being blocked by large TV sets, metal cubicle walls in open space offices, etc.

Even though the radio supports repeater mode, the two Gigabit Ethernet ports give you the ability to extend your network with cables, even if PoE power is required: the cAP XL ac supports 802.3af/at PoE input on the first port and passive PoE output (up to 57V) on the second port.

Vendor Homepage: mikrotik.com/product/cap_xl_ac | 10Base-T / 100Base-TX / 1000Base-T: 2 | Model name: cAP XL ac | Network Device Type: Wireless Access Point | Data transmission speed: 867 | Wireless Frequency Range: 2.4 and 5 GHz | Power supply requirements: PoE; adapter | Dimensions: D191 x 42 mm | Units per Shipping Box: 1 | Unit Calculated Volume: 0.003642 | Product Net Weight: 0.7 | Unit Calculated Weight: 0.85