



Power Supply
GIGABYTE GP-
P750BS 750
Watts Efficiency
80 PLUS
BRONZE PFC
Active MTBF
100000 hours
GP-P750BS

Modelis: GP-P750BS

Gamintojas: GIGABYTE

EAN: 4719331555238

Prekės kodas: 79190

64.99€

Ensure reliable and efficient power delivery with GIGABYTE power supplies. Designed for peak performance and durability, our PSUs offer stable and consistent energy to power your high-performance systems. With advanced protections and high-quality components, GIGABYTE power supplies provide the confidence you need for seamless, uninterrupted computing experiences.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- 80 PLUS Bronze certified (230V EU)
- 120mm Silent Fluid Dynamic Bearing (FDB) fan
- Soft-textured embossed cables
- Single +12V rail
- OVP/OPP/SCP/UVP/OCP/OTP protection

Summary: GIGABYTE P750BS Power Supply - PCI-E 6+2 Pin x 4, 80 PLUS Bronze, 120mm Fan, ATX compatible, EU Plug. Total power: 750 W, AC input voltage: 200 - 240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 150,500 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Bronze. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 140 mm, Height: 86 mm | Vendor Homepage: <https://www.gigabyte.com/> | AC input frequency: 50/60 | AC input voltage: 200 - 240 | Combined power (+12V): 750 | Combined power (+3.3V): 100 | Combined power (+5V): 100 | Combined power (+5Vsb): 15 | Combined power (-12V): 3.6 | Efficiency: 88 | Hold time: 16 | Input current: 6 | Max output current (+12V): 62.5 | Max output current (+3.3V): 20 | Max output current (+5V): 20 | Max output current (+5Vsb): 3 | Max output current (-12V): 0.3 | Power factor: 0.9 | Power Factor Correction (PFC) type: Active | Power Good signal delay range: 100 - 150 | Power protection features: Over current/Over power/Over voltage/Overheating/Short circuit/Under voltage | Total power: 750 | ATX power connector (20+4 pin): Yes | Cabling type: Non-Modular | CPU power connector (4+4 pin): Yes | Floppy disk drive connector: Yes | Floppy drive power connector: 2 | Motherboard power cable length: 600 | Motherboard power connector: 20+4 pin ATX | Number of SATA power connectors: 7 | PCI Express connector: Yes | PCI Express power connectors (6+2 pin): 4 | Peripheral (Molex) power cable length: 150/600 | Peripheral (Molex) power connectors (4-pin): 2 | SATA power cable length: 150/500 | 80 PLUS certification: 80 PLUS Bronze | Bearing technology: FDB | Mean time between failures (MTBF): 100000 | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | Fan location: Top | Number of fans: 1 | On/off switch: Yes | Product colour: Black | Depth: 140 | Height: 86 | Weight: 2218 | Width: 150 | Package depth: 206 | Package height: 117 | Package type: Box | Package weight: 2682 | Package width: 254 | Warranty period: 3 | Model name: GP-P750BS | Units per Shipping Box: 5 | Unit Calculated Volume: 0.007868 | Unit Calculated Weight: 2.15