



I/O HUB USB-C 9IN1 5GBPS/0.2M HMC-8HLSA AXAGON



Modelis: HMC-8HLSA

Gamintojas: AXAGON

EAN: 8595247907523

Prekės kodas: 79203

53.99€

AXAGON HMC-8HLSA

The multi-port USB-C 5Gbps AXAGON HMC-8HLSA hub 9in1 expands your laptop, computer or phone with nine ports. You can easily and quickly connect a monitor, three USB devices, Gigabit Ethernet network, headphones with microphone and an SD card reader to your computer at the same time via the double-sided USB-C connector. You also get the possibility to supply laptop using Power Delivery technology at the same time. The port replicator will thus provide you with a simple and compact 9-in-1 docking station not only for Windows laptops but also for Apple laptops such as MacBook Air or MacBook Pro.

The USB hub offers three USB outputs with standard USB-A connectors. Two of them with 5Gbps speed and one with 480Mbps speed for mouse or keyboard connection. The hub can also handle the

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

permanent connection of multiple external drives at the same time. Transfer rate up to 5Gb/s thanks to the fast USB 3.2 Gen 1 interface.

The USB-C connector is reserved only for charging of phone or laptops using Power Delivery 3.0 technology with a power of up to 100W. Connect a suitable USB-C Power Delivery charger into the hub and connect the hub to a laptop that supports Power Delivery. This will also free up one USB-C port on your laptop.

HDMI output provides high quality image up to 4K/60Hz Ultra HD resolution and supports multi-channel audio transmission. High frequencies at popular gaming resolutions of 2K/144Hz or FullHD/240Hz are also supported.

Thanks to HDR (high dynamic range) support, you can enjoy a significantly expanded range of colours and contrasts without restrictions. For video outputs to work properly, the laptop must have a USB-C port with DisplayPort Alternate Mode (DP Alt Mode) support or a Thunderbolt 3 port, Thunderbolt 4 and above.

Gigabit network card extends your computer by a fast and stable network connection, adds the missing RJ-45 network connector or another network card. Card reader supports all versions of SD and microSD cards including SDXC and microSDXC with capacity up to 2TB. The card reader enables simultaneous handling of cards in both slots and direct copying between them. The audio output is connected to a 3.5 mm jack and allows the connection of stereo headphones with a microphone.

The elegant aluminum body ensures not only mechanical resistance, but also passive cooling. Thanks to the Plug and Play and Hot Plug functions, connecting the hub itself is very simple without complicated installation, and peripherals can also be easily connected and disconnected while the computer is running. The hub does not afraid of connection to phones with a USB-C connector. For example, you can connect a flash drive, keyboard, mouse, monitor TV or projector to the phone.

Input (laptop connection):

- USB 5Gbps (USB 3.2 Gen 1 / USB 3.0), USB-C female connector.
- Compatible with USB 3.2 Gen 2, USB4 and Thunderbolt 3/4.

Input (power supply):

- USB Power Delivery 3.0 - 100W (only for charging), USB-C female connector.
- Charging of the notebook from the power adapter via USB-C hub.
- PD power must be supported by both the laptop (phone) and the wall charger.

USB outputs:

- 2x USB 5Gbps port, USB-A female connector.
- 1x USB 480Mbps port, USB-A female connector.
- USB-C hub can handle connecting multiple external drives at the same time.

Video output:

- 1x HDMI A port, HDMI A female connector.
- 4K resolution 4096 x 2160 at up to 60Hz.
- 2K / WQHD resolution 2560 x 1440 at up to 120Hz.
- FHD resolution 1920 x 1080 at up to 240Hz.
- Support for the above max. supported resolutions and frequencies requires connection to a computer with DisplayPort version 1.4.
- For the video output function, the hub must be connected to a USB-C port supporting DisplayPort Alternate Mode (DP Alt Mode) or to a USB-C port supporting Thunderbolt 3/4. A suitable OS is also required. The video output function will not be available without these requirements.
- HDR support (High dynamic range, 10 bit support) - realistic reproduction of light and dark details.
- HPD (Hot-Plug-Detect) support.
- TMDS (Transition Minimized Differential Signalling) support.
- HDCP 1.4 and 2.3 (High-bandwidth Digital Content Protection) full support.
- Support for 2-channel audio sampling rate up to 192 kHz and up to 24-bit audio - depends on source and end device, i.e. laptop/phone and TV/monitor/AV receiver.

RJ-45 output:

- Gigabit Ethernet interface with RJ-45 connector for UTP, FTP, STP or SFTP patch cable connection.
- Supported transmission rates for the Ethernet interface 10/100/1000 Mb/s.
- Supported IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T specifications.
- 10/100/1000 Mb/s auto-detection.
- Wake-on-LAN support.

The card reader - two slots:

- Slot Micro SD: microSD / microSDHC / microSDXC / TransFlash.
- Slot SD: SecureDigital / SDHC / SDXC, MultiMedia Card, MMC, MMC Dual Voltage, MMC mobile, RS-MMC, with adapter - miniSD, microSD / microSDHC / microSDXC, MMC Micro.
- UHS-I support. Speed up to 104 MB/s. Support hardware ECC function and CRC function.
- 2 LUN - the reader is indicated as two disk drives. The possibility of copying from card to card.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Audio output / input:

- 1x 3.5 mm jack for headset, headphones or active speakers,
- 2-channel analog stereo output 48 kHz @ 16 bit for playback,
- 1-channel analog mono microphone input 48 kHz @ 16 bit for recording.

Other features:

- Possibility to connect your device while running thanks to the Hot Plug support.
- Full Plug and Play support.
- Standby mode support.
- Power via USB bus - USB bus power or from PD wall charger.
- Heavy-duty aluminium body for better hub cooling.
- The blue LED indicates with constant light the hub connection to the computer.
- The high-quality shielded cable ensures high communication speed and minimal undesirable interference.
- Dimensions 118 x 46 x 15 mm.
- Weight 88 g.
- USB-C male cable length 20 cm.

Supported operating systems:

- Microsoft Windows 10 / 11 and later, macOS, Linux, Chrome OS and Android.
- Compatibility depends on used OS and support from device manufacturer.
- DisplayPort Alternate Mode (DP Alt Mode) is only supported in updated OS and also depends on support from device (notebook, phone).
- Graphics card drivers may also affect the correct operation of the product. We recommend downloading the latest version of drivers.

Package contains:

- USB-C hub with fixed 20 cm long cable,
- multilingual guide CZ / DE / DK / ENG / ESP / FIN / FR / GR / HR / HU / IT / NL / PL / PT / RO / RU / SK / SWE / BG / CN / TR / ARA,
- packed in a cardboard box with a hanging hole.

Vendor Homepage: www.axagon.eu/en/produkty/hmc-8hlsa | Audio port: 1 | HDMI: 1 | MicroSD Card Slot: 1 | RJ45: 1 | SD Card Slot: 1 | USB 3.0: 3 | Dimensions: 118 x 46 x 15 mm | Units per Shipping Box: 1 | Unit Calculated Volume: 0.000693 | Product Net Weight: 0.088 | Unit Calculated Weight: 0.14

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903