

3M 4910F25 mounting tape/label 33 m

Gamintojas: **3M** · Modelis: **4910F25** · EAN: **4001895594120** · Prekės kodas: **801381**



223,90 €

Kaina su PVM

Be PVM: **185,04 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Quick and easy to apply - bonds in seconds
- ✓ High temperature resistant - retaining excellent bonding performance
- ✓ Versatile - bonds to most high surface energy substrates including metal, glass and high surface energy plastics
- ✓ Clear, acrylic construction for joining transparent material
- ✓ Tape Dimensions - 25mm x 33m
- ✓ Sold as single roll
- ✓ Creates a permanent seal against water, moisture and more
- ✓ Allows the use of thinner, lighter weight and dissimilar materials
- ✓ Clear material is ideal for joining transparent material

Aprašymas

Recommended for use with 3M VHB Surface Cleaner, 3M VHB Applicator Pads and 3M VHB Roller, as detailed in the application guidelines. 3M's VHB Tape provides immediate handling strength by bonding in seconds. It's quick and easy to apply with no mess or waste. As a result, the solution offers unrivalled time saving benefits and enables fabricators to complete the bonding process in house. This allows them to have complete control of the manufacture, resulting in improved production efficiency. What's more, with VHB Tape, preparation of surfaces is much easier and safer, with no need to use strong chemicals. And that means less mess and fewer issues with health and safety in the work environment. **IMPORTANT:** Before applying 3M VHB Tape please click here to review surface preparation and application instructions The information provided is based on 3M experience. In all cases full testing should be carried out to determine suitability for intended use.

Replace screws, rivets and studs when bonding with 3M™ VHB™ Tape 4910. Our tape bonds and seals transparent materials on contact with no drying. It's virtually invisible and helps keep surfaces smooth with no unsightly rivet or weld marks. It spreads stress load across length of the joint and with high dynamic stress absorption reduces vibration and impact stress.

Techninė specifikacija

Features	
Product type	Mounting tape
Product colour	Red
Length	33 m
Proper use	Indoor, Indoor & outdoor
Suitable for materials	Glass, Metal, Plastic
Temperature (max)	149 °C
Easy to use	Yes
Weight & dimensions	
Width	25 mm
Packaging content	
Quantity	1
Matmenys ir svoris	
Svoris	0,02kg

Gamintojo ir saugos informacija

GAMINTOJAS	ATSAKINGAS ASMUO ES	PLATINTOJAS
3M	3M Nederland B.V.	MB KOMPIUTERIŲ GURU
	Schenkkade 50K, 2595 AR Den Haag, NL	V. Nagevičiaus g. 3, LT-08237 Vilnius
	3mnederland.nl	info@shopro.lt