

StarTech.com 3ft (1m) DB9 to 3.5mm Serial Cable for Serial Device Configuration, RS232 DB9 Male to 3.5mm Cable Used for Calibrating Projectors, Digital Signage, TVs via Audio Jack

Gamintojas: **STARTECH** · Modelis: **9M351M-RS232-CABLE** · EAN: **065030893565** · Prekės kodas: **801619**



14,90 €

Kaina su PVM

Be PVM: **12,31 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **DB9 TO 3.5 MM SERIAL CABLE:** 3ft (1m) RS232 serial control cable enables configuration or calibration of a 3.5mm RS-232 serial devices - Use with TVs, projectors, digital signage displays requiring 3-conductor RS-232 serial control through 3.5mm audio jack
- ✓ **QUALITY CONSTRUCTION:** High quality 28 AWG copper wires with Al-Mylar cable shielding and shielded metal shell connectors prevent EMI interference - Molded PVC connectors with strain reliefs and PVC jacket prevent damage due to bends or rough usage
- ✓ **COMPATIBILITY:** The DB9 to 3.5mm cable works with USB-A and USB-C to DB9 serial adapters (1P3FP-USB-SERIAL / ICUSB232C) for computers that do not have a built-in serial port / Note: DB9 gender changer may be required such as our GC9SF (not included)
- ✓ **SPECIFICATIONS:** Length: 3.3ft (1m) - DB9 Male to 3.5 mm Male Serial Cable - Color: Black - 28 AWG - OD: 3.5mm - Jacket: PVC - DB9 Pin 3 to 3.5mm Tip - DB9 Pin 2 to 3.5mm Ring - DB9 Pin 5 to 3.5mm Sleeve
- ✓ **THE IT PRO'S CHOICE:** Designed and built for IT Professionals, this product is backed for life, including free lifetime 24/5 multi-lingual technical assistance



Aprašymas

Connect a DB9 enabled control unit to a 3.5mm enabled device for RS-232 based control

This serial cable features male DB-9 and 3.5mm connectors. It enables remote serial RS232 calibration of TVs, projectors, and digital signage devices that feature a 3.5mm audio jack.

High Quality Construction

The aluminum-mylar cable shielding and metal shell connectors mitigate EMI. The molded PVC connectors with strain reliefs and PVC cable jacket prevent damage caused by strain and/or abrasion.

Secure the DB-9 connector by tightening the integrated thumbscrews. These connector screw locks prevent accidental disconnection which could lead to data loss/corruption.

DB9 Serial to 3.5mm Pinout

DB9 Pin 3 to 3.5mm Tip

DB9 Pin 2 to 3.5mm Ring

DB9 Pin 5 to 3.5mm Sleeve

This product is backed for life, including free lifetime 24/5 multi-lingual technical assistance.

Techninė specifikacija

Ports & interfaces

Connector 1	DB-9
Connector 2	3.5mm
Connector 1 gender	Male
Connector 2 gender	Male
Connector 1 form factor	Straight
Connector 2 form factor	Straight
Cable length	1 m

Performance

Product colour	Black
Cable jacket material	Polyvinyl chloride (PVC)
AWG wire size	28

Operational conditions

Operating temperature (T-T)	-20 - 60 °C
Storage temperature (T-T)	-20 - 60 °C
Relative humidity	30 - 75%

Certificates

Compliance certificates	RoHS
Packaging data	
Package width	128 mm
Package depth	220 mm
Package height	10 mm
Package weight	23 g
Technical details	
Cable diameter	3.5 mm
Logistics data	
Products per master (outer) case	120 pc(s)
Master (outer) case width	388 mm
Master (outer) case length	340 mm
Master (outer) case height	310 mm
Sustainability	
Sustainability compliance	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	15,00cm × 12,00cm × 2,00cm
Svoris	0,05kg

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS	ATSAKINGAS ASMUO ES	PLATINTOJAS
StarTech.com Ltd.	StarTech.com Limited	MB KOMPIUTERIŲ GURU
Artisans Crescent 45, N5V 5E9 Ontario, London, CA	Laarderhoogtweg 25, 1101 EB Amsterdam, NL	V. Nagevičiaus g. 3, LT-08237 Vilnius
startech.com	startech.com	info@shopro.lt