ACT USB-C multiport adapter for 1 HDMI monitor, 1x USB-A, PD pass-through

Gamintojas: **ACT** · Modelis: **AC7022** · EAN: **8716065437492** · Prekės kodas: **802436**



47,90 €

Kaina su PVM

Be PVM: **39,59 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Solid aluminium USB-C 3.2 Gen1 to HDMI video adapter with a max. resolution of 4096 x 2160 (4K) @30Hz
- ✓ 60W Power Delivery Pass-Through port for charging your connected device
- ✓ USB-A 3.2 Gen1 data port
- ✓ Plug and play: a USB-C port with DisplayPort Alternate Mode (DP Alt Mode) is needed







Aprašymas

Use the USB-C 3.2 Gen1 to HDMI 4K adapter to connect a HMDI screen or beamer to a notebook. The adapter supports a maximum resolution of 4096 x 2160 (4K) @ 30Hz. The AC7022 has a Power Delivery Pass-Through port (max. 60W) and an additional USB-A port.

Connect a notebook with USB-C to a monitor or beamer with HDMI

Connect a source device with USB-C to a monitor or beamer with HDMI by using the USB-C 3.2 Gen1 to HDMI adapter. The USB-C port of the source device must support DP Alt Mode. The USB-C to HDMI Adapter supports the maximum resolution of 4096 x 2160 (4K) @ 30Hz. The AC7022 has an additional USB-A data port.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

USB-C Power Delivery Pass-Through port 60W

The USB-C Pass-Through port supports power delivery 60W. The notebook is always charged with the right amount of power thanks to the pre-defined Power Delivery profiles. The charger communicates with the notebook to negotiate the most effective charging profile.

Techninė specifikacija

Performance	
USB version	3.2 Gen 1 (3.1 Gen 1)
DVI output	No
HDMI output	Yes
DisplayPort output	No
USB connector type	USB Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Maximum resolution	4096 x 2160 pixels
Supported graphics resolutions	1920 x 1080 (HD 1080), 3840 x 2160
Design	
Product colour	Grey
Housing material	Aluminium
Integrated USB cable	Yes
Power	
Output voltage	12.0V (2.58A), 15.0V (2.67A), 20.0V (2.75A), 5.0V (2.0A), 9.0V (2.44A)
Weight & dimensions	
Width	125 mm
Depth	160 mm
Height	25 mm
Weight	89 g
USB cable length	0.12 m
Logistics data	
Harmonized System (HS) code	84733020
Matmenys ir svoris	
Svoris	1,00kg

Dokumentai ir vaizdo įrašai

› Vaizdo įrašas objects.icecat.biz/objects/81617324_20594931.mp4

Gamintojo ir saugos informacija

GAMINTOJAS

Intronics BV
Koolhovenstraat 1E, 3772 MT Barneveld, NL
intronics.nl

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt