

StarTech.com Gigabit Ethernet Fiber Media Converter with Open SFP Slot

Gamintojas: **STARTECH.COM** · Modelis: **ET91000SFP2** · EAN: **065030852517** · Prekės kodas: **803176**



263,90 €

Kaina su PVM

Be PVM: **218,10 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Wired
- ✓ 1250 Mbit/s
- ✓ Ethernet LAN (RJ-45) ports: 1
- ✓ Fiber ports quantity: 1 SFP
- ✓ Black



Aprašymas

Convert and extend a Gigabit Ethernet connection over fiber using the Gigabit SFP of your choice

The ET91000SFP2 Open SFP Fiber Media Converter converts and extends a Gigabit Ethernet connection over fiber, using the Gigabit SFP of your choice.

A versatile solution for connecting an Ethernet (1000Base-T) network to remote network segments over a fiber backbone, the media converter features an open SFP slot that lets you choose the MSA-Compliant Gigabit SFP that best suits your fiber connection mode (single / multi-mode) and distance requirements (see our full line of for compatible solutions).

The fiber to Ethernet converter has a durable all-steel chassis and offers simple plug-and-play installation, while support for full-duplex operation and Jumbo Frame support provides efficient network operation.

For added versatility, this Gigabit media converter supports standalone operation, or installation into the 20 Slot, ETCHS2U" text="2U Rackmount Chassis (ETCHS2U). For applications where multiple chassis-mounted media converters are required, this Gigabit media converter can be purchased as a ET91000SFP2C" text="Card Module only (ET91000SFP2C).

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

The StarTech.com Advantage

- Install the SFP of your choice with the open SFP slot
- Operate as a standalone media converter or install into the ETCHS2U chassis
- Ensure maximum up-time with link-loss forwarding and remote status monitoring

Techninė specifikacija

Network	
Maximum data transfer rate	1250 Mbit/s
Converter input interface	1000Base-T
Converter output interface	1000Base-LX, 1000Base-SX
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3z
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	1000 Mbit/s
Auto MDI/MDI-X	Yes
Duplex system	Full, Half
Performance	
Mean time between failures (MTBF)	65000 h
Features	
Internal	No
LED indicators	Yes
Product colour	Black
Housing material	Steel
Ports & interfaces	
Fiber optic connector	SFP
Connectivity technology	Wired
Ethernet LAN (RJ-45) ports	1
Fiber ports quantity	1
Power	
Input voltage	100 - 240 V
Input current	0.36 A
Output voltage	12 V

Output current	1 A
Power consumption (typical)	8 W
Power over Ethernet (PoE)	No
External power adapter	Yes
Weight & dimensions	
Width	95 mm
Depth	160 mm
Height	20 mm
Weight	400 g
Operational conditions	
Operating temperature (T-T)	0 - 60 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Packaging content	
Manual	Yes
Packaging data	
Package width	137 mm
Package depth	208 mm
Package height	92 mm
Package weight	786 g
Certificates	
Compliance certificates	RoHS
Certification	FCC
Logistics data	
Harmonized System (HS) code	85176990

Gamintojo ir saugos informacija

GAMINTOJAS

StarTech.com Ltd.

Artisans Crescent 45, N5V 5E9 Ontario, London,
CA
startech.com

ATSAKINGAS ASMUO ES

StarTech.com Limited

Laarderhoogtweg 25, 1101 EB Amsterdam, NL
startech.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt