LevelOne 16-Port PS/2-USB VGA KVM Switch

Gamintojas: **LEVELONE** · Modelis: **KVM-3216** · EAN: **4015867229392** · Prekės kodas: **803423**



641,91 €

Kaina su PVM

Be PVM: **530,50 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports video resolutions up to 2048 x 1536
- ✓ Numerical LED display and LED indicators for easy bank/port status monitoring
- ✓ Autoscan period programmable 10 ~ 95 through OSD Menu option
- ✓ Control and manage 16 computers or up to 256 computers via daisy chain function
- ✓ Enhanced PS/2 mouse reset hotkeys for non-PnP OS such as Win NT 4.0 and Linux
- ✓ Buzzer sound for hotkey and port switching confirmation
- ✓ Password protection
- ✓ Active Sync Replication for DDC emulation
- ✓ Auto-logout timeout support





Aprašymas

The LevelOne KVM-3216 16-port combo KVM switch enables users to control and manage a server farm or computers connected to the KVM switch with either the local console or remote console port.Local ConsoleThe KVM-3216 Combo KVM Switch is easy to connect to a keyboard and mouse with a VGA monitor through the local console port. This enables a user to control systems connected to the KVM switch directly.Remote ConsoleIn order to make use of the remote control feature.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Techninė specifikacija

Ports & interfaces	
Number of computers controlled	16
Keyboard port type	USB, PS/2
Mouse port type	USB, PS/2
Video port type	VGA
Console ports	PS/2, VGA (D-Sub), USB A
VGA (D-Sub) ports quantity	16
Console USB ports quantity	2
PS/2 ports quantity	2
DC-in jack	Yes
Performance	
Maximum resolution	2048 x 1536 pixels
Scan interval	35,70,10,40,80,15,45,90,20,50,25,55,30,60 s
Auto scan delay (min)	10 s
Auto scan delay (max)	95 s
Design	
Rack mounting	Yes
Product colour	Black
Rack capacity	1U
Housing material	Metal
Cascadable	Yes
LED indicators	Power
Push button	Yes
Hot keys	Yes
Display	
Built-in display	No
On Screen Display (OSD)	Yes
Power	
Power source	DC
Input voltage	9 V
Input current	1 A
External power adapter	Yes
System requirements	

Windows operating systems supported	Windows 7 Professional x64, Windows Vista Enterprise x64, Windows 7 Starter, Windows Vista Home Basic, Windows 7 Starter x64, Windows Vista Home Basic x64, Windows 7 Ultimate, Windows 95, Windows Vista Home Premium, Windows 2000, Windows 7 Ultimate x64, Windows 98, Windows Vista Home Premium x64, Windows 7 x64, Windows 98SE, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows 7, Windows ME, Windows Vista x64, Windows 7 Enterprise, Windows XP, Windows 7 Enterprise x64, Windows XP Home, Windows 7 Home Basic, Windows XP Home x64, Windows 7 Home Basic x64, Windows Vista, Windows XP Professional, Windows 7 Home Premium, Windows Vista Business, Windows XP Professional x64, Windows 7 Home Premium x64, Windows Vista Business x64, Windows 7 Professional, Windows Vista Enterprise
Linux operating systems supported	Yes
Mac operating systems supported	Yes

Sustainability

Compliance certificates	Federal Communications Commission (FCC), UKCA, WEEE, CE
Sustainability compliance	Yes

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	0 - 85%
Storage relative humidity (H-H)	0 - 90%

Weight & dimensions

Width	410 mm
Depth	165 mm
Height	44.5 mm
Weight	1.97 kg

Packaging data

Package width	567 mm
Package depth	245 mm
Package height	106 mm
Package weight	3.01 kg
Package type	Box

Packaging content

Manual	Yes
AC adapter included	Yes

Technical details

Pallet gross length	110 cm
Pallet gross width	120 cm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Pallet height (air)	11.5 cm
Logistics data	
Master (outer) cases per pallet (air)	24 pc(s)
Master (outer) case width	585 mm
Master (outer) case length	270 mm
Master (outer) case height	545 mm
Master (outer) case gross weight	15.7 kg
Products per master (outer) case	5 pc(s)
Country of origin	Taiwan

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas
- CE ženklinimas

Gamintojo ir saugos informacija

GAMINTOJAS

LevelOne

ATSAKINGAS ASMUO ES

Digital Data Communications GmbH
Im Defdahl 10 F, 44141 Dortmund, DE
level1.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Saugos dokumentai

- CE ženklinimas