

ATEN KE9900ST KVM extender Transmitter

Gamintojas: **ATEN** · Modelis: **KE9900ST** · EAN: **4719264647567** · Prekės kodas: **804210**



859,90 €

Kaina su PVM

Be PVM: **710,66 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Advance processor provides lossless and low latency video transmissions up to 1920 x 1200 @ 60Hz; 24-bit color depth
- ✓ Support standard HDMI resolutions from 640 x 480 up to 1920 x 1200
- ✓ High speed USB Storage Transmission support
- ✓ Compliant with DP 1.2 and HDCP 1.3
- ✓ Auto-MDIX – automatically detects cable type
- ✓ Built-in 8KV/15KV ESD protection and 1KV surge protection
- ✓ Slim, light and fanless design for silent operations that are energy efficient
- ✓ Support connection via Gigabit Ethernet port
- ✓ Rack Mountable and Wall Mountable



Aprašymas

The KE9900ST Slim DisplayPort KVM over IP Extender is a compact and affordable high performance IP-based transmitter which can be paired with any KE Series* receiver for a savings solution that stays within budget. The KE Series* extenders allow access to a computer system from a remote USB console over an intranet, enabling users to locate computers in a secure and temperature controlled environment, which is isolated from users' workstation.

The KE9900ST supports DisplayPort video input from the computer while the paired KE Series receiver supports DisplayPort, DVI or HDMI monitor output, providing video resolutions up to 1920 x 1200 and flawless and lossless video compression quality with minimal latency. The extender also supports RS-232 serial commands. In addition to a DC power jack, the KE9900ST transmitter includes an extra DC terminal block for convenient installation.

The KE9900ST can be set on a desk, mounted on a wall or at the rear of a rack with its space-saving 0U rack mount design. Moreover, the KE9900ST can be used as a point-to-point / point-to-multipoint / multipoint-to-point extender, or integrated into a KVM over IP Matrix System (multipoint-to-multipoint) when combined with the KVM over IP Matrix Manager (CCKM), providing more flexible applications in different working environments.

The KE9900ST can be configured through the CCKM or RS-232/Telnet text menu. The KVM over IP extender also offers enhanced security features such as supporting AES encryption for secured Video / Keyboard / Mouse / USB data transmissions and RADIUS / LDAP / AD or remote user authentication that provides an added layer of connection security.

When integrated with the CCKM and paired with the KE Series receiver, the KVM over IP extender supports more advanced features such as boundless switching, fast switching, video wall, multi display, profile scheduling, auto detection of all KE Series extenders on the same subnet for the sake of fast installation or configuration, as well as username / password authentication and authorization. Please refer to the CCKM webpage for more details.

Whether you're configuring, monitoring, administrating, controlling or extending computer access, the KVM over IP Matrix System is made adaptable, to fit an endless variety of working environments and workstation settings, as well as to provide solutions in broadcasting, control center, multimedia, manufacturing and many other industries where matrix extending is required.

*Please visit www.aten.com for a comprehensive list of the KVM over IP extenders.

Techninė specifikacija

Features	
Type	Transmitter
Connectivity technology	Wired
Cable types supported	Cat5e
Rack mounting	Yes
Maximum digital resolution	1920 x 1200 pixels
Colour depth	24 bit
Product colour	Black
Material	Metal
LED indicators	Yes
Transmitter	
Transmitter video port type	DisplayPort

Number of displays supported	1
Transmitter local keyboard/mouse port type	USB
RJ-45 ports quantity (transmitter)	1
Ports & interfaces	
RS-232 ports	1
Weight & dimensions	
Transmitter width	18.2 cm
Transmitter depth	11.8 cm
Transmitter height	2.87 cm
Transmitter weight	650 g
Packaging content	
AC adapter included	Yes
Cables included	DisplayPort, USB
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 95%
Technical details	
Weight	1.04 kg

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.

Datung Road No.125, Sec. 2, 221 New Taipei City, TW

aten.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt