ATEN CE775 AV extender AV transmitter & receiver Black

Gamintojas: **ATEN** · Modelis: **CE775** · EAN: **4710423778511** · Prekės kodas: **804229**



839,90 €

Kaina su PVM

Be PVM: **694,13 €**

Sandėlyje

Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dual View Support - connect two screens to transmit two video output signals to a remote site up to 300 m away using inexpensive Cat 5e/6 cables
- ✓ Dual Console operation - control your system from both the local and remote USB keyboard, monitor, and mouse consoles
- ✓ Deskew Function – automatically synchronizes the time delay of RGB signals to compensate for distance
- ✓ PC Wakeup support - from the remote console, simply use a pushbutton to wake a computer at the local site via RS-232
- ✓ Superior video quality – 1920x1200@60Hz(150 m), 1280x1024@60Hz(300 m)
- ✓ Gain/Compensation Control – adjusts signal strength in order to compensate for distance
- ✓ On Screen Display – conveniently adjust video quality with the intuitive OSD menu system
- ✓ RS-232 Channel – allow you to connect to a serial terminal, or serial devices such as touchscreens and barcode scanners
- ✓ Built-in 8KV/15KV ESD protection (Contact voltage 8KV; Air voltage 15KV)
- ✓ Sun/Mac keyboard support and emulation *





Aprašymas

ATEN CE775 Dual View KVM Extenders with Deskew function allows access to a computer system from a remote Dual View console up to 300 m away. The dual view function provides support for two displays, allowing the video output to seamlessly display on two monitors. Its advanced PC Wake - Up feature that allows you simply uses a pushbutton from the remote dual view console to wake a PC at the local site via RS-232, no need to go to the local site to wake up the PC. It eliminates the need for traveling back and forth between the local computer and remote console, effi cient

and flexible.

Use the improved built-in front panel tuners to easily adjust the picture quality. In addition, you can automatically synchronize the time delay of RGB signals in order to compensate for distance, easy and fast than ever.

Techninė specifikacija

Features	
Type	AV transmitter & receiver
Maximum resolution	1920 x 1200 pixels
Cable types supported	Cat5e
Maximum transfer distance	300 m
Audio system	Multichannel
LED indicators	Yes
Product colour	Black
Ports & interfaces	
RJ-45 input ports	2
RJ-45 output ports	2
VGA (D-Sub) input ports	4
Audio input	3.5mm
Audio output	3.5mm
DC-in jack	Yes
Power	
Operating voltage	5.3 V
External power adapter	Yes
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Dimensions (WxDxH)	75.8 x 200 x 42 mm
Weight	690 g
Technical details	
Connector type	USB, SPHD-17, RS-232

Dokumentai ir vaizdo įrašai

› Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.

Datung Road No.125, Sec. 2, 221 New Taipei City, TW

aten.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt