

ATEN 32-Port Cat 5e/6 KVM Switch

Gamintojas: **ATEN** · Modelis: **KH1532A** · EAN: **4719264646096** · Prekės kodas: **808427**



1 016,90 €

Kaina su PVM

Be PVM: **840,41 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ One KVM console controls up to 32 directly connected computers
- ✓ Superior Video Quality- Supports the video resolutions up to 1920 x 1200 @60Hz for up to 30 meters, 1600 x 1200 @60Hz for up to 40 meters, and 1280 x 1024 @75Hz for up to 50 meters
- ✓ By daisy chaining up to 31 additional KH1532A switches, as many as 1024 computers can be controlled from the original KVM console
- ✓ Three port selection methods: Manual (via front panel pushbuttons), Hotkey, and multi-language OSD (On Screen Display)



Aprašymas

The KH1532A KVM switches are control units that allow IT administrators to access and control multiple computers from a single PS/2 or USB KVM console (keyboard, monitor, and mouse). Operators can take control of up to 32 (KH1532A) computers. By daisy chaining up to 31 additional switches, as many as 1024 computers can be controlled from a central KVM console.

- 1x KH1532A Cat 5 High-Density KVM Switch
- 1x LIN5-04A2-J11G Firmware Upgrade Cable
- 1x LIN2-418K-E12G Power Cord
- 1x Rack Mount Kit
- 1x Foot Pad Set (4 pcs.)
- 1x User Instructions

Techninė specifikacija

Ports & interfaces	
Number of computers controlled	32
Keyboard port type	USB, PS/2
Mouse port type	USB, PS/2
Video port type	VGA
Console ports	PS/2, USB A, VGA (D-Sub)
VGA (D-Sub) ports quantity	1
Console USB ports quantity	2
USB connector type	USB Type-A
PS/2 ports quantity	2
Network	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	32
Performance	
HD type	Full HD
Maximum resolution	1920 x 1200 pixels
Scan interval	1,255 s
Daisy chain	Yes
Number of users	10 user(s)
Firmware upgradeable	Yes
Design	
Rack mounting	Yes
Product colour	Black
Rack capacity	1U
Housing material	Metal
LED indicators	Yes
Push button	Yes
Hot keys	Yes
Display	
Built-in display	No
On Screen Display (OSD)	Yes
Power	
Power source	AC

Input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Input current	1 A
Power consumption (typical)	4.8 W
Sustainability	
Compliance certificates	RoHS
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Weight & dimensions	
Width	437.2 mm
Depth	163.7 mm
Height	44 mm
Weight	3.26 kg
Packaging data	
Package width	131 mm
Package depth	540 mm
Package height	233 mm
Package weight	3.75 kg
Packaging content	
Cables included	AC
Manual	Yes
Rack mount kit	Yes
Logistics data	
Master (outer) case net weight	9.78 kg
Harmonized System (HS) code	85176200
Master (outer) case width	420 mm
Master (outer) case length	565 mm
Master (outer) case height	258 mm
Master (outer) case gross weight	11.9 kg
Products per master (outer) case	3 pc(s)
Matmenys ir svoris	
Svoris	3,65kg

Dokumentai ir vaizdo įrašai

- › Naudojimo instrukcija
- › Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

ATEN INTERNATIONAL CO., LTD.

Datung Road No.125, Sec. 2, 221 New Taipei City, TW

aten.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt