

Lindy 100m Fibre Optic USB 3.2 Type C Extender

Gamintojas: **LINDY** · Modelis: **43312** · EAN: **4002888433129** · Prekės kodas: **808652**



468,90 €

Kaina su PVM

Be PVM: **387,52 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Extends USB 3.2 Gen 2 connections up to 100m
- ✓ Supports data transfer rates up to 10Gbps
- ✓ Uses standard andldquo;off the shelfandrdquo; LC duplex fibre cabling
- ✓ Resistant to RF and EM Interference for use in highly sensitive areas
- ✓ 2 year warranty



Aprašymas

Fibre Optic USB extenders allow USB signals to be extended far beyond the limits of traditional copper cable solutions. The Lindy 100m Fibre Optic USB 3.2 Type C Extender supports SuperSpeed transfer rates of up to 10Gbps. This Extender is a complete and compact two-part hardware solution comprising of a transmitter that connects directly to the user's computer and receiver that connects to the USB peripheral, using andldquo;off the shelfandrdquo; LC duplex fibre cabling.

The extender is ideal for long distance use with remote desktop links, industrial control systems, surveillance control rooms and external storage applications. This device is fully compatible with, and can be used to extend signals from, 4K USB webcams and video conferencing systems. Utilising fibre optic transmission, this extender provides high resistance to EMI and RFI, perfect for use in andldquo;noisyandrdquo; areas such as hospitals, large retail installations or industrial buildings. The Fibre Optic USB 3.2 Type C Extender is supplied with a USB Type A to Micro-B cable which can be attached to a second USB port or to a USB Power supply (not included) should additional power be required.

Please note that DisplayPort Alternate Mode is not supported.

Please note: This Extender is not backwards compatible with USB 2.0.

Information about USB 3.0, 3.1 and 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface. USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps. USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Techninė specifikacija

Performance	
Type	Network transmitter & receiver
Maximum transfer distance	100 m
Data transfer rate	10000 Mbit/s
Cable types supported	Fiber
Ports & interfaces	
Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB Type-C ports quantity (transmitter)	1
USB Type-C ports quantity (receiver)	1
Design	
Product colour	Black
Housing material	Metal
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-10 - 70 °C
Operating relative humidity (H-H)	10 - 80%
Weight & dimensions	
Transmitter width	5.8 cm
Transmitter depth	2 cm
Transmitter height	9 mm
Transmitter weight	39 g
Receiver width	5.8 cm
Receiver depth	2 cm
Receiver height	9 mm
Receiver weight	39 g
Certificates	
Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS

Matmenys ir svoris

Svoris	0,32kg
--------	--------

Dokumentai ir vaizdo įrašai

[> Atitikties deklaracija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.

Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB

lindy.com

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH

Markircher Str. 22, 68229 Mannheim, DE

lindy.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt

Saugos dokumentai

[> Atitikties deklaracija](#)