

## Lindy 1m USB Type C to DP 8K60 Adapter Cable

Gamintojas: **LINDY** · Modelis: **43341** · EAN: **4002888433419** · Prekės kodas: **808682**



### 26,90 €

Kaina su PVM

Be PVM: **22,23 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite [www.shopro.lt](http://www.shopro.lt)

### Pagrindinės savybės

- ✓ Connects a 4K or 8K DP display to a computer equipped with a USB Type C port
- ✓ Supports DisplayPort resolutions up to 7680x4320@60Hz and 3840x2160@144Hz
- ✓ Perfect for connecting Macbooks (incl. Apple M1), laptops and PCs to modern DP displays
- ✓ Requires DisplayPort Alternate Mode support by the USB Port/Bus
- ✓ 2 year warranty



### Aprašymas

Lindy USB Type C to DisplayPort 8K60 Adapter Cable allows users to easily add external video capabilities to a computer featuring the USB Type C port with additional support for DisplayPort Alternate Mode. This DisplayPort connector of the adapter cable can be directly connected to the DisplayPort display with the 1m cable allowing for additional flexibility when positioning of the DP display - perfect for a simple and adaptable installation.

It supports video resolutions up to 7680x4320@60Hz and 3840x2160@144Hz, making it the ideal tool for 8K game streaming or high resolution 8K video editing. Additional support for High Dynamic Range ensures video content can be seen with enhanced brightness, superior contrasts and a much wider colour gamut for more lifelike colour. These cables are great for creating eye-catching retail displays, innovative working environments or immersive video playback in sports bars and home cinema installations, while support for uncompressed multi-channel audio allows for an

impressive three-dimensional surround sound performance to compliment detailed, clear video.

This cable is powered by the USB Bus, so no external power supply is needed and with 'Plug and Play' installation, this converter cable can be installed into an AV system with minimum difficulty, ideal for both professional and first time users.

## Techninė specifikacija

| Features                           |                                       |
|------------------------------------|---------------------------------------|
| Cable length                       | 1 m                                   |
| Connector 1                        | USB Type-C                            |
| Connector 2                        | DisplayPort                           |
| Connector 1 gender                 | Male                                  |
| Connector 2 gender                 | Male                                  |
| Connector 1 form factor            | Straight                              |
| Connector 2 form factor            | Straight                              |
| Connector contacts plating         | Nickel                                |
| Power source                       | USB                                   |
| High Dynamic Range (HDR) supported | Yes                                   |
| Maximum resolution                 | 7680 x 4320 pixels                    |
| Data transfer rate                 | 32.4 Gbit/s                           |
| Maximum refresh rate               | 144 Hz                                |
| Bend radius (min)                  | 2.55 cm                               |
| Cable material                     | Copper                                |
| Product colour                     | Black                                 |
| Nominal attenuation                | 0.1MHz-6MHz                           |
| Attenuation (max)                  | 6MHz                                  |
| Chipset                            | VL100                                 |
| Jacket material                    | Acrylonitrile butadiene styrene (ABS) |
| Connector housing material         | Polyvinyl chloride (PVC)              |
| Contact material                   | Copper                                |
| AWG wire size                      | 34                                    |
| Operational conditions             |                                       |
| Operating temperature (T-T)        | -20 - 40 °C                           |
| Storage temperature (T-T)          | -40 - 80 °C                           |
| Certificates                       |                                       |
| Compliance certificates            | CE, REACH, RoHS                       |
| Packaging data                     |                                       |

|              |         |
|--------------|---------|
| Package type | Polybag |
|--------------|---------|

**Packaging content**

|                   |         |
|-------------------|---------|
| Quantity per pack | 1 pc(s) |
|-------------------|---------|

**Logistics data**

|                             |          |
|-----------------------------|----------|
| Harmonized System (HS) code | 84733080 |
|-----------------------------|----------|

**Matmenys ir svoris**

|        |        |
|--------|--------|
| Svoris | 0,06kg |
|--------|--------|

**Dokumentai ir vaizdo įrašai**[› Naudojimo instrukcija](#)**Gamintojo ir saugos informacija**

## GAMINTOJAS

**LINDY International Ltd.**

Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB

[lindy.com](http://lindy.com)

## ATSAKINGAS ASMUO ES

**LINDY-Elektronik GmbH**

Markircher Str. 22, 68229 Mannheim, DE

[lindy.com](http://lindy.com)

## PLATINTOJAS

**MB KOMPIUTERIŲ GURU**

V. Nagevičiaus g. 3, LT-08237 Vilnius

[info@shopro.lt](mailto:info@shopro.lt)