

Lindy 50m 2 Port USB 2.0 Cat. 6 Extender

Gamintojas: **LINDY** · Modelis: **43386** · EAN: **4002888433860** · Prekės kodas: **809268**



129,91 €

Kaina su PVM

Be PVM: **107,36 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Extend 2 USB 2.0 ports up to 50m using low cost Cat.6 network cable (not included)
- ✓ Bi-directional PoC (Power over Cable) requires a power supply connection from only one side of the installation
- ✓ Supports USB 2.0 High Speed and USB 1.1 Full Speed / Low Speed
- ✓ Plug and Play installation
- ✓ 2 year warranty



Aprašymas

This Lindy USB 2.0 Cat.6 Extender can be used to extend the distance between two USB peripheral devices and the host computer by up to 50m. A standard, low cost Cat.6 network cable (not included) is used to bridge the connection between the transmitter and the receiver unit. For best performance and compatibility, we recommend the use of solid core patched cables.

The Extender features bidirectional Power over Cable (PoC) functionality, which provides additional flexibility. This allows power to be supplied alongside data through Cat.6 network cable in a point-to-point connection between the transmitter and receiver, meaning only a single power supply is required at the transmitter or receiver unit.

With robust metal housing and integrated mounting brackets this Extender is the ideal solution for industrial environments.

Techninė specifikacija

Performance	
Type	Network transmitter & receiver
Maximum transfer distance	50 m
Data transfer rate	480 Mbit/s
Cable types supported	Cat5e, Cat6
Chipset	NS1021
Plug and Play	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
RJ-45 ports quantity (transmitter)	1
RJ-45 ports quantity (receiver)	1
USB 2.0 ports quantity	3
DC-in jack	Yes
RJ-45 input ports	1
RJ-45 output ports	1
Design	
Product colour	Black
Quantity per pack	1 pc(s)
Power	
Input current	2 A
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 125 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 90%
Weight & dimensions	
Transmitter width	6.02 cm
Transmitter depth	6.7 cm
Transmitter height	2.37 cm
Transmitter weight	195 g
Receiver width	6.02 cm
Receiver depth	6.7 cm
Receiver height	2.6 cm

Receiver weight	195 g
-----------------	-------

Packaging content

Cables included	USB
-----------------	-----

Manual	Yes
--------	-----

AC adapter included	Yes
---------------------	-----

Certificates

Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS
-------------------------	--

Sustainability

Sustainability compliance	Yes
---------------------------	-----

Matmenys ir svoris

Svoris	0,57kg
--------	--------

Dokumentai ir vaizdo įrašai

› [Atitikties deklaracija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

LINDY International Ltd.

Sadler Forster Way Unit 103, TS17 9JY Stockton-on-Tees, GB

lindy.com

ATSAKINGAS ASMUO ES

LINDY-Elektronik GmbH

Markircher Str. 22, 68229 Mannheim, DE

lindy.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt

Saugos dokumentai

› [Atitikties deklaracija](#)